

# Carton Compression Tester 10KN 20KN 50KN Servo Control Compression

## **Testing Machine**







#### Product Details:

Place of Origin: China

Brand Name: YUYANG

• Certification: GB/T4857.4 GB/T4857.16 ISO2872 ASTM D642 TAPPI-T804 JIS-Z0212.

Model Number: YY1415

#### Payment & Shipping Terms:

Minimum Order Quantity: 1 set

• Price: **Negotiation** 

Packaging Details: Plywood Case

Delivery Time: 10-15 work days

Payment Terms: T/T L/C Western Union

Supply Ability: 2 sets per month

Share to :

# Carton Compression Package Testing Equipment 10KN 20KN 50KN Servo Control

#### **Application:**

Apply for compression resistance, deformation, stacking test of package container such as corrugated paper box and honeycomb box, and also the wooden package box.

#### Standards:

GB/T4857.4, GB/T4857.16, ISO2872, ASTM D642, TAPPI-T804, JIS-Z0212.

#### Introduction:

Computer Control Box Compression Tester used for measuring the pressure strength of cartons, containers, etc, for inspecting the pressure-resistance and strike- endurance of packing materials during transportation or carry.

#### **Characteristics:**

- 1. Adopting windows platform, all the parameter settings can be processed in the dialog box, and it operates easily.
- 2. Using a single-screen operation, do not need to switch the screen.
- 3. with three languages in simplified Chinese, traditional Chinese and English, the software interface can be switched easily.
- 4. Choosing translational, overlapping mode at the same time to make sure a number of curve date comparison.
- 5. With a variety of measurement units, measure in imperial and metric are switchable.
- 6. Also, this paper tube compression test equipment has automatic magnification function, in order to achieve the most appropriate size of the graphics.
- 7. With an advanced design of machine structure which have strong rigidness and small volume but light weight.
- 8. It can do test of compression strength, stack strength and peak value.

### **Specifications:**

Capacity	500kg, 1000kg, 2000kg, 5000kg or customize
Resolution	1/100,000
Correctness of force	Better than ±1%
Correctness of distortion reading	Better than ±1%
Effectual range of testing force	1~100%F.S
Unit	kgf,gf ,N,kN,lbf
Test space	1000×1000mm (can customize)
Space between platen	1000mm (can customize)
Drive System	servo system,precision ball screw, DC variable speed drive system
Test speed	0.01~500mm/min, keyboard inputing
Return speed	500mm/min
Power	1φ,220V±10% 50Hz
Stop mode	Set limits of security, urgent stop key, programable force and elongation setting, specimen damage sensing



