

# KERN CD50-3P1

Load cells made of stainless steel

**KERN**<sup>®</sup>



## Piktogramme

### STANDARD



IP 68



1 DAY

## Measuring system

|                                    |         |
|------------------------------------|---------|
| Combined Error:                    | 0,023 % |
| Load cell connection:              | 4-wire  |
| Nominal sensitivity:               | 2       |
| OIML class:                        | C3      |
| Resolution Load cell à Verifiable: | 3000 e  |
| Weighing capacity [Max]:           | 50 t    |
| Y value:                           | 10000   |

## Environmental conditions

|                                |        |
|--------------------------------|--------|
| Maximum operating temperature: | 65 °C  |
| Maximum operating temperature: | 40 °C  |
| Minimum ambient temperature:   | -35 °C |
| Minimum operating temperature: | -10 °C |

## Category

|        |        |
|--------|--------|
| Brand: | Sauter |
|--------|--------|

## Packaging & shipping

|                               |                    |
|-------------------------------|--------------------|
| Delivery:                     | 48 h               |
| Dimensions packaging (WxDxH): | 215 x 220 x 160 mm |
| Gross weight:                 | 3,200 kg           |
| Net weight:                   | 2,706 kg           |
| Shipping method:              | Parcel service     |

## Construction

|               |      |
|---------------|------|
| Cable length: | 15 m |
|---------------|------|