

## WE 17-125 Quick RT (601086000) Angle Grinder (220-240 V / 50 - 60 Hz); Cardboard box

Order no. 601086000 EAN 4007430311641



Product may differ from Image



- Maximum productivity thanks to top performance with low weight
- Perfect ergonomics thanks to slim handle for maximum control and easy working overhead
- Metabo Marathon-motor with new cooling and carbon brush system for twice the service life
- Tacho Constamatic (TC) Full-wave Electronics: fast work progress by means of constant speed under load
- M-Quick System for tool-free disc change at the touch of a button
- Tool-free adjustable guard; twist-proof
- Low-vibration side handle Metabo VibraTech (MVT)
- Metabo S-automatic mechanical safety clutch: minimises kick-back to the lowest level when the disc jams unexpectedly for maximum user safety and swift progress
- Electronic soft start and restart protection
- Gear housing can be unscrewed, rotated in 90° steps and remounted for left-handed operation or cutting
- Auto-stop carbon brushes to protect the motor



## Technical data

## Characteristics

| Grinding wheel Ø             | 125 mm / 5 "         |
|------------------------------|----------------------|
| Rated input power            | 1750 W               |
| Output power                 | 1070 W               |
| No-load speed                | 11000 rpm            |
| Revolutions at rated load    | 11000 rpm            |
| Torque                       | 3.8 Nm / 34 in-lbs   |
| Spindle thread               | M 14                 |
| Weight (without power cable) | 2.5 kg / 5.5 lbs     |
| Cable length                 | 4 m / 13 ft          |
| Vibration                    |                      |
| Surface grinding             | 6.8 m/s²             |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Grinding with sandpaper      | 3 m/s <sup>2</sup>   |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |
| Noise emission               |                      |
| Sound pressure level         | 92 dB(A)             |
| Sound power level (LwA)      | 103 dB(A)            |
| Uncertainty of measurement K | 3 dB(A)              |

## Scope of delivery

Guard Metabo VibraTech (MVT) side handle Inner support flange M-Quick flange nut