

## WEPBA 24-230 MVT Quick (606481000) Angle Grinder (220-240 V / 50 - 60 Hz); Cardboard box; with mechanical disc brake

Order no. 606481000 EAN 4007430337641



Product may differ from Image

















- Metabo Marathon motor with patented dust protection for long service life
- Highest degree of user safety thanks to mechanical disc brake and deadman's switch: disc stop in 2.5 seconds after releasing even in case of a power cut
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly for high user safety
- Reduced vibrations for low-fatigue working thanks to Metabo VibraTech (MVT) damping system and integrated Autobalancer
- Rotating back handle and side handle can be mounted at 3 positions for optimum handle position also when cutting
- Metabo Quick for tool-free disc change by means of a quick-locking nut
- Tool-free adjustable guard; twist-proof
- Starting current limitation prevents the actuation of the lock on start-up
- Electronic overload protection and restart protection
- Metabo safety switch prevents unintentional start
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



Technical data	
Characteristics	
Grinding wheel Ø	230 mm / 9 "
Rated input power	2400 W
Output power	1600 W
No-load speed	6600 rpm
Revolutions at rated load	4600 rpm
Torque	17 Nm / 150 in-lbs Nm
Spindle thread	M 14
Weight (without power cable)	6.2 kg / 13.7 lbs
Cable length	4 m / 13 ft
Vibration	
Surface grinding	3.9 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Grinding with sandpaper	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Noise emission	
Sound pressure level	94 dB(A)
Sound power level (LwA)	105 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Guard

Metabo VibraTech (MVT) side handle

Inner support flange

Quick-locking nut

www.metabo.com 2/2