

## WEPBA 26-230 MVT Quick (606482000) Angle Grinder (220-240 V / 50 - 60 Hz); Cardboard box; with mechanical disc brake

Order no. 606482000 EAN 4007430337665



Product may differ from Image

















- Metabo Marathon motor with patented dust protection for long service life
- Highest degree of user safety thanks to mechanical disc brake and deadman's switch: disc stop in 2.5 seconds after releasing even in case of a power cut
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly for high user safety
- Reduced vibrations for low-fatigue working thanks to Metabo VibraTech (MVT) damping system and integrated Autobalancer
- Rotating back handle and side handle can be mounted at 3 positions for optimum handle position also when cutting
- Metabo Quick for tool-free disc change by means of a quick-locking nut
- Tool-free adjustable guard; twist-proof
- Starting current limitation prevents the actuation of the lock on start-up
- Electronic overload protection and restart protection
- Metabo safety switch prevents unintentional start
- Auto-stop carbon brushes to protect the motor

www.metabo.com 1/2



| Technical data               |                       |
|------------------------------|-----------------------|
| Characteristics              |                       |
| Grinding wheel Ø             | 230 mm / 9 "          |
| Rated input power            | 2600 W                |
| Output power                 | 1800 W                |
| No-load speed                | 6600 rpm              |
| Revolutions at rated load    | 4800 rpm              |
| Torque                       | 18 Nm / 160 in-lbs Nm |
| Spindle thread               | M 14                  |
| Weight (without power cable) | 6.6 kg / 14.6 lbs     |
| Cable length                 | 4 m / 13 ft           |
| Vibration                    |                       |
| Surface grinding             | 3.7 m/s <sup>2</sup>  |
| Uncertainty of measurement K | 1.5 m/s²              |
| Grinding with sandpaper      | 2.5 m/s <sup>2</sup>  |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup>  |
| Noise emission               |                       |
| Sound pressure level         | 95 dB(A)              |
| Sound power level (LwA)      | 106 dB(A)             |
| Uncertainty of measurement K | 3 dB(A)               |

## Scope of delivery

Guard

Metabo VibraTech (MVT) side handle

Inner support flange

Quick-locking nut

www.metabo.com 2/2