

WB 18 LTX BL 125 Quick (613077660) Cordless Angle Grinders 18V 2x5.5Ah LiHD; Charger ASC 145 (220-240 V / 50 - 60 Hz); Plastic Carry Case

Order no. 613077660 EAN 4007430289094



Product may differ from Image



- Unique encapsulated Metabo brushless motor with optimum protection from dust provides quick work progress and the highest efficiency
- Slim design for prolonged comfort when working overhead or in areas with limited space
- Fast brake system for highest user safety stops the disc within a matter of seconds after switching off
- Metabo Quick for tool-free disc change by means of a quick-locking nut
- Tool-free adjustable guard; twist-proof
- Battery pack can be swivelled for better access in hard to reach places
- Electronic safety shutdown: reduces kickback if the disc stops unexpectedly for high user safety
- Overload protection: protects the motor from overheating
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after battery pack change
- Detachable dust protection filter protects motor from coarse particles
- LiHD battery pack for ultimate performance, extremely long runtime and service life
- Ultra-M technology: highest performance, gentle charging and 3 years of warranty on the battery pack.
- Battery packs with capacity display for checking the charge status



Technical data

Characteristics

Type of battery pack	LiHD	
Battery pack capacity	2 x 5.5 Ah	
Battery voltage	18 V	
Grinding wheel Ø	125 mm / 5 "	
No-load speed	9000 rpm	
Spindle thread	M 14	
Weight (including battery pack)	2.7 kg / 6 lbs	
Vibration		
Surface grinding	5 m/s ²	
Uncertainty of measurement K	2.5 m/s ²	
Grinding with sandpaper	2.5 m/s ²	
Uncertainty of measurement K	1.5 m/s²	
Noise emission		
Sound pressure level	82 dB(A)	
Sound power level (LwA)	93 dB(A)	
Uncertainty of measurement K	3 dB(A)	

Scope of delivery

Guard Side handle Dust protection filter 2 LiHD battery packs (18 V/5.5 Ah) Quick charger ASC 145 "AIR COOLED" Charger ASC 145 "AIR COOLED" Plastic carry case Inner support flange Quick-locking nut