

BE 500/10 (600353000) Drill
(220-240 V / 50 - 60 Hz); Cardboard box

Order no. 600353000
EAN 4007430262011



Product may differ from Image

- Handy drill especially for demanding metal processing
- Optimal speed range for precise drilling into steel up to Ø 10 mm
- Robust die cast aluminium gear housing for optimum heat dissipation and durability
- Particularly compact design with small width across corners
- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Forward and reverse rotation
- Keyless chuck and spindle stop for convenient one-handed tool change
- Futuro top keyless chuck: automatic retightening when drilling for precise drilling results
- Handle with non-slip soft-grip surface

Technical data

Characteristics

Rated input power	500 W
Output power	250 W
Drill Ø steel	10 mm / 3/8 "
Drill-Ø soft wood	30 mm / 1 3/16 "
No-load speed	0 - 1600 rpm
Revolutions at rated load	1000 rpm
Gears	1
Maximum torque	16 Nm / 142 in-lbs
Collar diameter	43 mm / 1 11/16 "
Chuck capacity	1 - 13 mm // 1/32 - 1/2 "
Drill spindle with hexagonal recess	6.35 mm / 1/4 "
Drill spindle thread	1/2 " - 20 UNF
Weight (without power cable)	1.8 kg / 4 lbs kg
Cable length	4 m / 13 ft

Vibration

Drilling in metal	2.1 m/s ²
Uncertainty of measurement K	1.5 m/s ²

Noise emission

Sound pressure level	80 dB(A)
Sound power level (LwA)	91 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Futuro Top keyless chuck
Side handle
Open-jawed spanner