

**BE 75 Quick (600585700) Drill**  
**(220-240 V / 50 - 60 Hz); MetaLoc**

Order no. 600585700  
EAN 4007430220967



Product may differ from Image



- Suitable for drilling with large diameters and for heavy screw jointing in wood without pre-drilling
- Metabo "Quick" System: quick change of tool holder and bits for flexible working
- Robust die cast aluminium gear housing for optimum heat dissipation and durability
- Rotating carbon brush bridge for maximum performance even in anti-clockwise operation, e.g. for the removal of stubborn screws
- Vario (V)-Electronics for working at customised speeds to suit various application materials
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Forward and reverse rotation
- Spindle with hexagonal recess for screwdriver bits for working without chuck

## Technical data

### Characteristics

Rated input power	750 W
Output power	470 W
Drill Ø steel	16 mm / 5/8 "
Drill-Ø soft wood	50 mm / 2 "
No-load speed	0 - 660 rpm
Revolutions at rated load	350 rpm
Gears	1
Maximum torque	75 Nm / 664 in-lbs
Collar diameter	43 mm / 1 11/16 "
Chuck capacity	1.5 - 13 mm // 1/16 - 1/2 "
Drill spindle with hexagonal recess	6.35 mm / 1/4 "
Weight (without power cable)	2.6 kg / 5.7 lbs kg
Cable length	4 m / 13 ft

### Vibration

Drilling in metal	2.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

### Noise emission

Sound pressure level	81 dB(A)
Sound power level (LwA)	92 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Geared quick change chuck  
 Chuck key  
 long side handle  
 MetaLoc case  
 Quick-change bit holder  
 Quick-change angle adapter