

BS 18 LTX BL Q I (602351660) Cordless Drill / Screwdriver
18V 2x5.5Ah LiHD; Charger ASC 145 (220-240 V / 50 - 60 Hz); Plastic Carry Case

Order no. 602351660
EAN 4007430298171



Product may differ from Image



- Brushless drill/screwdriver with maximum power for demanding applications
- Metabo Quick System: quick change of bit retainer and bits, for flexible working
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Unique Metabo brushless motor for quick work progress and highest efficiency when drilling and screwdriving
- Precision Stop: electronic torque control with increased precision for accurate and intricate working
- Spindle with hexagonal recess for screwdriver bits for working without chuck
- Collar (Ø 43 mm) for versatile use
- Integrated working light to illuminate the contact area
- Robust die cast aluminium gear housing for optimum heat dissipation and long service life
- Handy belt hook and bit holder can be fixed either on the right or left side
- LiHD battery pack for ultimate performance, extremely long runtime and service life
- Battery packs with capacity display for checking the charge status
- Ultra-M technology: highest performance, gentle charging and 3 years of warranty on the battery pack.

Technical data

Characteristics

| | |
|---------------------------------|-----------------------------|
| Type of battery pack | LiHD |
| Battery voltage | 18 V |
| Battery pack capacity | 2 x 5.5 Ah |
| Maximum torque - soft | 60 Nm / 531 in-lbs |
| Pulse torque | 65 Nm / 48 ft. lbs |
| Maximum torque, hard | 120 Nm / 1062 in-lbs |
| Adjustable torque | 1 - 20 Nm // 9 - 177 in-lbs |
| Drill Ø steel | 13 mm / 1/2 " |
| Drill-Ø soft wood | 65 mm / 2 1/2 " |
| No-load speed | 0 - 500 / 0 - 1850 rpm |
| Chuck capacity | 1.5 - 13 mm // 1/16 - 1/2 " |
| Weight (including battery pack) | 2.5 kg / 5.5 lbs |

Vibration

| | |
|-----------------------------|----------------------|
| Drilling in metal | 3.2 m/s ² |
| Screwdriving without impact | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|----------|
| Sound pressure level | 78 dB(A) |
| Sound power level (LwA) | 89 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Quick-change chuck
 Belt hook and bit case
 2 LiHD battery packs (18 V/5.5 Ah)
 Quick charger ASC 145 "AIR COOLED"
 Charger ASC 145 "AIR COOLED"
 Plastic carry case
 Quick-change bit holder
 Side handle