

SB 18 LTX BL Q I (602353500) Cordless Hammer Drill 18V 2x4Ah Li-ion; Charger ASC 55 (220-240 V / 50 - 60 Hz); Plastic Carry Case

Order no. 602353500 EAN 4007430297891



Product may differ from Image











- Brushless hamemr drill with maximum power for demanding applications
- Metabo Quick System: quick change of bit retainer and bits, for flexible working
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Unique Metabo brushless motor for quick work progress and highest efficiency when drilling and screwdriving
- Precision Stop: electronic torque control with increased precision for precise, delicate working
- High-performance impact mechanism for optimum drilling performance
- Spindle with hexagonal recess for screwdriver bits for working without chuck
- Collar (Ø 43 mm) for versatile use
- Integrated working light to illuminate the contact area
- · Robust die cast aluminium gear housing for optimum heat dissipation and long service life
- With handy belt hook and bit case which can be fixed either on the right or left side
- Battery packs with capacity display for checking the charge status
- Ultra-M technology: highest performance, gentle charging and 3 years of warranty on the battery pack.

www.metabo.com 1/2



Technical data	
Characteristics	
Type of battery pack	Li-ion
Battery voltage	18 V
Battery pack capacity	2 x 4 Ah
Maximum torque - soft	60 Nm / 531 in-lbs
Pulse torque	60 Nm / 48 ft. lbs
Maximum torque, hard	120 Nm / 1062 in-lbs
Adjustable torque	1 - 20 Nm // 9 - 177 in-lbs
Drill-Ø masonry	16 mm / 5/8 "
Drill Ø steel	13 mm / 1/2 "
Drill-Ø soft wood	65 mm / 2 1/2 "
No-load speed	0 - 500 / 0 - 1850 rpm
Maximum impact rate	32300 bpm
Chuck capacity	1.5 - 13 mm // 1/16 - 1/2 "
Weight (including battery pack)	2.4 kg / 5.3 lbs
Vibration	
Drilling in metal	3.2 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Impact drilling concrete	20.7 m/s ²
Uncertainty of measurement K	1.5 m/s ²
Noise emission	
Sound pressure level	92 dB(A)
Sound power level (LwA)	103 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Quick-change chuck

Belt hook and bit case

2 Li-Power battery packs (18 V/4.0 Ah)

Charger ASC 55 "AIR COOLED"

Plastic carry case

Quick-change bit holder

Side handle

www.metabo.com 2/2