

**SSD 18 LTX 200 BL (602396800) Cordless Impact Driver**  
**18V 2x4Ah LiHD; Charger ASC 55 (220-240 V / 50 - 60 Hz); Plastic Carry Case**

Order no. 602396800  
EAN 4007430334992



Product may differ from Image



- Compact cordless impact driver with 1/4" hexagon socket and 200 Nm
- Unique Metabo brushless motor for quick work progress and highest efficiency for any application
- Automatic Power Shift (APS) supports working with self-tapping screws: automatic torque reduction after drilling to prevent overtightening.
- Twelve speed/torque levels for a wide range of applications
- Integrated work light for illumination of the work area
- Robust die cast aluminium gear housing for optimum heat dissipation and durability
- Handy belt hook, can be fixed either on the right or left side
- LiHD battery pack for ultimate performance, extremely long runtime and service life
- Battery packs with capacity display for checking the charge status
- Ultra-M technology: highest performance, gentle charging and 3 years of warranty on the battery pack.

## Technical data

### Characteristics

|                                 |                               |
|---------------------------------|-------------------------------|
| Type of battery pack            | LiHD                          |
| Battery voltage                 | 18 V                          |
| Battery pack capacity           | 2 x 4 Ah                      |
| Max. screw size                 | M16                           |
| Max. no-load speed              | 2900 rpm                      |
| Maximum impact rate             | 4000 bpm                      |
| Maximum torque                  | 200 Nm / 150 ft. lbs          |
| Speed/torque levels             | 12                            |
| Bit retainer                    | Hexagon recess 1/4" (6.35 mm) |
| Weight (including battery pack) | 1.4 kg / 3.1 lbs              |

### Vibration

|                              |                      |
|------------------------------|----------------------|
| Impact screwdriving          | 9 m/s <sup>2</sup>   |
| Uncertainty of measurement K | 1.5 m/s <sup>2</sup> |

### Noise emission

|                              |           |
|------------------------------|-----------|
| Sound pressure level         | 94 dB(A)  |
| Sound power level (LwA)      | 105 dB(A) |
| Uncertainty of measurement K | 3 dB(A)   |

## Scope of delivery

Belt Hook  
Plastic carry case  
2 LiHD Battery packs (18 V/4.0 Ah)  
Charger ASC 55 "AIR COOLED"