

SSW 18 LTX 400 BL (602205660) Cordless Impact Wrench 18V 2x5.5Ah LiHD; Charger ASC 145 (220-240 V / 50 - 60 Hz); Plastic Carry Case

Order no. 602205660 EAN 4007430330994



Product may differ from Image

- Unique Metabo brushless motor for quick work progress and highest efficiency for any application
- Overload protection: protects the motor from overheating
- High torque accompanied by an exceptionally compact design
- High torque machine with low kick-back torque
- Twelve speed/torque levels for a wide range of applications
- Integrated work light for illumination of the work area
- Robust die cast aluminium gear housing for optimum heat dissipation and durability
- Handy belt hook, can be fixed either on the right or left side
- LiHD battery pack for ultimate performance, extremely long runtime and service life
- Battery packs with capacity display for checking the charge status
- Ultra-M technology: highest performance, gentle charging and 3 years of warranty on the battery pack.



Technical data

Characteristics

| Type of battery pack | LiHD |
|---------------------------------|-----------------------------|
| Battery voltage | 18 V |
| Battery pack capacity | 2 x 5.5 Ah |
| Max. screw size | M20 |
| Max. no-load speed | 0 - 2150 rpm |
| Maximum impact rate | 4250 bpm |
| Maximum torque | 400 Nm / 295 ft. lbs |
| Max. loosening torque | 620 Nm / 420 ft. lbs |
| Speed/torque levels | 12 |
| Bit retainer | Male square 1/2" (12.70 mm) |
| Weight (including battery pack) | 2.2 kg / 4.8 lbs |
| Vibration | |
| Impact screwdriving | 12 m/s² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Noise emission | |
| Sound pressure level | 100 dB(A) |
| Sound power level (LwA) | 111 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Belt Hook Plastic carry case 2 LiHD battery packs (18 V/5.5 Ah) Quick charger ASC 145 "AIR COOLED" Charger ASC 145 "AIR COOLED"