

2 Safety Tester

Impulse/Surge Tester

7700/7710/7720



Key Feature

- Low power pulses test function
- Low power non-destructive test
- Automatic Level Control Function
- Waveform comparison

- 8 Channels (7720)
- Multiple winding test function
- Provide statistic and print functions
- Measure voltage up to 10,000V (7710)

Accessory

- Standard**
- Power cord
 - User manual CD
 - HV Test Cable

- Optional**
- RS-232 Cable
 - Remote Cable
 - D-Sub Footswitch

Measuring Item

Flutter	Waveform comparison
Area comparison	Corona
Total Area	

Specification

7700	2 Channels
7710	2 Channels
7720	8 Channels
7700/7720 Impluse Voltage	200V-5000V (programmable)
7710 Impluse Voltage	200V-10000V (programmable)
Impulse Voltage Accuracy	±2%
Measuring Time	50mS

General

Power Supply	98-132Vac or 192-264Vac
Display	320*240 dot-matrix display
Interface	RS-232, Print Port, Remote Control, GPIB (option)
Flash Memory	200 sets
Operation	Auto, Manual
Environment	Temperature: 10 ~ 40°C, Humidity: 20 ~ 90%RH
Dimension (W*H*D)	435x145x522 mm.....7700/7710 435x190x522 mm.....7720
Weight	8 Kg7700/7710 9 Kg7720