

**KHE 5-40 (600687000) Combination Hammer**  
(220-240 V / 50 - 60 Hz); Plastic Carry Case

Order no. 600687000  
EAN 4007430259158



Product may differ from Image



- Combination hammer with 2 functions: hammer drilling and chiselling
- Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user's health
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for work with materials requiring customised speeds, which remain constant under load
- Thumbwheel for preselection of the speed and impact rate
- Electronic soft start for precise spot-drilling
- Optimum heat dissipation and low weight thanks to die cast magnesium gear housing
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Wear Indication for Carbon Brush

## Technical data

### Characteristics

Max. single blow energy (EPTA)	7.5 J
Maximum impact rate	3200 bpm
Rated input power	1010 W
Drill-Ø concrete with hammer drills	40 mm / 1 9/16 "
Drill-Ø masonry with core bits	90 mm / 3 9/16 "
No-load speed	200 - 350 rpm
Bit retainer	SDS-max
Collar diameter	60 mm / 2 3/8 "
Weight (without power cable)	6.2 kg / 13.7 lbs
Cable length	4 m / 13 ft

### Vibration

Hammer drilling concrete	13.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>
Chiseling	11.5 m/s <sup>2</sup>
Uncertainty of measurement K	1.5 m/s <sup>2</sup>

### Noise emission

Sound pressure level	95 dB(A)
Sound power level (LWA)	106 dB(A)
Uncertainty of measurement K	3 dB(A)

## Scope of delivery

Metabo VibraTech (MVT) side handle  
 Duster  
 Plastic carry case  
 Drilling depth guide  
 Lubricant for tool shank end