

KHE 96 (600596000) Combination Hammer (220-240 V / 50 - 60 Hz); Plastic Carry Case

Order no. 600596000 EAN 4007430167088



Product may differ from Image









- Combination hammer with 2 functions: hammer drilling and chiselling
- Metabo VibraTech (MVT): integrated damping system to reduce vibrations in order to protect the user's health
- Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for work with materials requiring customised speeds, which remain constant under load
- Thumbwheel for preselection of the speed and impact rate
- Electronic soft start for precise spot-drilling
- Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly
- Wear Indication for Carbon Brush
- Lockable switch for comfortable working in continuous operation

www.metabo.com 1/2



Technical data	
Characteristics	
Max. single blow energy (EPTA)	20 J
Maximum impact rate	1950 bpm
Rated input power	1700 W
Drill-Ø concrete with hammer drills	50 mm / 2 "
No-load speed	125 - 250 rpm
Bit retainer	SDS-max
Collar diameter	73 mm / 2 7/8 "
Weight (without power cable)	11.8 kg / 26 lbs
Cable length	6 m / 20 ft
Vibration	
Hammer drilling concrete	12.4 m/s ²
Uncertainty of measurement K	2 m/s ²
Chiseling	11 m/s²
Uncertainty of measurement K	2 m/s ²
Noise emission	
Sound pressure level	100 dB(A)
Sound power level (LwA)	111 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Metabo VibraTech (MVT) side handle Plastic carry case Lubricant for tool shank end Duster

www.metabo.com 2 / 2