

FLOW CONE APPARATUS

Model Number : GOTT-FCA-01



DESCRIPTION

GOTT-FCA-01 is used for viscosity and fluidity determinations of mortars, muds, grouts, pre-stressing tendons, fluid materials, etc. Cone top diameter is 155 mm, total length 290 mm, capacity 1700 cc. Mortar fluidity is considered suitable when the flow time of 1000 cc of mortar is comprised between 17 to 25 seconds.

ADDITIONAL ITEMS

cup.	CODE
INTERCHANGEABLE NOZZLE DIA	300-356
Interchangeable nozzle \varnothing 13 mm	
SIEVE, 150MM,DIA	CODE
	300-357
SIEVE, \varnothing 150 mm, 1.5 mm mesh opening that fits the upper cone.	

Manuals :

- (1) All manuals are written in English
- (2) Model Answer
- (3) Teaching Manuals

General Terms :

- (1) Accessories will be provided where applicable.
- (2) Manuals & Training will be provided where applicable.
- (3) Designs & Specifications are subject to change without notice.
- (4) We reserve the right to discontinue the manufacturing of any product.

Warranty :

2 Years

ORDERING INFORMATION :

ITEM	MODEL NUMBER	CODE
FLOW CONE APPARATUS	GOTT-FCA-01	300-355

* Proposed design only, subject to changes without any notice.