

BS 18 LTX Impuls (602191500) Cordless Drill / Screwdriver
18V 2x4Ah Li-ion; Charger ASC 55 (220-240 V / 50 - 60 Hz); Plastic Carry Case

Order no. 602191500
EAN 4007430238818



Product may differ from image



- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Powerful Metabo 4-pole motor for fast drilling and screwdriving
- Overload protection: protects the motor from overheating
- Spindle with hexagonal recess for screwdriver bits for working without chuck
- Collar (Ø 43 mm) for versatile use
- Integrated working light to illuminate the contact area
- Robust die cast aluminium gear housing for optimum heat dissipation and long service life
- Handy belt hook and bit holder can be fixed either on the right or left side
- Battery packs with capacity display for checking the charge status
- Ultra-M technology: highest performance, gentle charging and 3 years of warranty on the battery pack.

Technical data

Characteristics

| | |
|---------------------------------|--------------------------------|
| Type of battery pack | Li-ion |
| Battery voltage | 18 V |
| Battery pack capacity | 2 x 4 Ah |
| Maximum torque - soft | 55 Nm / 487 in-lbs |
| Pulse torque | 60 Nm / 531 in-lbs |
| Maximum torque, hard | 110 Nm / 974 in-lbs |
| Adjustable torque | 1.5 - 24 Nm // 13 - 221 in-lbs |
| Drill Ø steel | 13 mm / 1/2 " |
| Drill-Ø soft wood | 65 mm / 2 1/2 " |
| No-load speed | 0 - 500 / 0 - 1700 rpm |
| Chuck capacity | 1.5 - 13 mm // 1/16 - 1/2 " |
| Weight (including battery pack) | 2.3 kg / 5.1 lbs |

Vibration

| | |
|------------------------------|----------------------|
| Drilling in metal | 2.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |
| Screwdriving without impact | 2.5 m/s ² |
| Uncertainty of measurement K | 1.5 m/s ² |

Noise emission

| | |
|------------------------------|----------|
| Sound pressure level | 80 dB(A) |
| Sound power level (LwA) | 91 dB(A) |
| Uncertainty of measurement K | 3 dB(A) |

Scope of delivery

Futuro Plus keyless chuck with metal sleeve
 2 Li-Power battery packs (18 V/4.0 Ah)
 Charger ASC 55 "AIR COOLED"
 Plastic carry case
 Side handle
 Belt hook and bit case