CS 23-355 (602335000) Metal Chop Saw

(220-240 V / 50 - 60 Hz); Cardboard box

Order no. 602335000
EAN 4007430169204



Product may differ from Image

- For single phase alternating current
- Powerful and fast cutting for profiles, pipes and rods made of steel, cast iron, aluminium and other non-ferrous metals.
- Motor and gear with ball bearing for high loads
- Spindle lock for easy disc change
- Quick clamping device with variable mitre conversion from -15° up to 45°
- Easy to transport due to built-in handle and locking device
- High safety thanks to swivelling cutting guard
- Storage for double-ended wrench at the machine table
- Safe working thanks to adjustable spark guide plate
- Adjustable cutting depth limiter

Technical data

Characteristics

Grinding wheels (Ø x bore)	355 x 25.4 mm / 14 x 1 "
Torque	18 Nm / 160 in-lbs
No-load speed	4000 rpm
Rated input power	2300 W
Cutting capacity steel bars	65 mm / 2 1/2 "
Cutting capacity pipes	125 mm / 5 "
Cutting capacity steel sections	115 x 130 mm / 4 1/2 x 5 1/8 "
Maximum opening of vice jaws	238 mm / 9 3/8 "
Dimensions of the base plate	468 x 282 mm / 18 7/16 x 11 3/32 "
Transport height	400 mm / 15 3/4 "
Weight	16.9 kg / 37 lbs
Cable length	2.7 m / 9 ft

Noise emission

Sound pressure level	91 dB(A)
Sound power level (LwA)	104 dB(A)
Uncertainty of measurement K	3 dB(A)

Scope of delivery

Open-ended ring spanner
Inner support flange
Flange nut