

DAIHAN-brand® Fabric-Housed Heating Mantles, (1) Self Standing-base & (2) Top Cover, 450°C, 50ml~100Lit. NEW

for Spherical Flask, with Nickel Chrome Heating Element, Option-Controller, with Certi. & Traceability

직물케이스 히팅맨틀, Ni-Cr열선 내장, 자력교반기와 사용가능, 조절기 별도

- Made in Korea
- Ideal for All type Round Flask and Use with Magnetic Stirrer
- with Certificate & Traceability : Controlled by Serial Number, Certificate, Delivery-information, and Traceable Data Base System
- Built-in Temp-Controller. Nickel-Chrome Heating Element "Coil-type" : Acid Resistant & Long Life Time.



(1) Self Standing-base

(1) Self Standing-base Mantle


Flasks, ml Dia. ϕ mm	Mantle			Catalog No.	
	Watts (W)	Inside Depth	Outside $\phi \times H$ (mm)	with 230V	with 120V
50ml, ϕ 49 ~ 52	90 W	30 mm	ϕ 100 \times H50	DH.WHM12110	DH.WHM12120
100ml, ϕ 63 ~ 66	90 W	50 mm	ϕ 120 \times H70	DH.WHM12111	DH.WHM12121
250ml, ϕ 83 ~ 86	160 W	55 mm	ϕ 150 \times H80	DH.WHM12112	DH.WHM12122
500ml, ϕ 102 ~ 105	250 W	75 mm	ϕ 180 \times H100	DH.WHM12113	DH.WHM12123
1,000ml, ϕ 130 ~ 133	350 W	90 mm	ϕ 210 \times H115	DH.WHM12114	DH.WHM12124
2,000ml, ϕ 165 ~ 169	490 W	105 mm	ϕ 250 \times H130	DH.WHM12115	DH.WHM12125
3,000ml, ϕ 184 ~ 187	600 W	115 mm	ϕ 270 \times H140	DH.WHM12116	DH.WHM12126
4,000ml, ϕ 206 ~ 208	750 W	120 mm	ϕ 310 \times H160	DH.WHM8108	DH.WHM8108.1
5,000ml, ϕ 221 ~ 224	850 W	135 mm	ϕ 310 \times H160	DH.WHM12117	DH.WHM12127
6,000ml, ϕ 234 ~ 237	850 W	135 mm	ϕ 310 \times H160	DH.WHM12118	DH.WHM12128
10Lit, ϕ 278 ~ 282	1,500 W	205 mm	ϕ 390 \times H260	DH.WHM12119	DH.WHM12129



<Ex.>(2) Top Cover
with (1) Self Standing-base

(2) Top Cover only

Flasks, ml Dia. ϕ mm	Mantle		Catalog No.	
	Watts (W)	Outside $\phi \times H$ (mm)	with 230V	with 120V
250ml, ϕ 83 ~ 86	90 W	ϕ 136 \times H70	DH.WHM121301	DH.WHM121311
500ml, ϕ 102 ~ 105	160 W	ϕ 160 \times H77	DH.WHM121302	DH.WHM121312
1,000ml, ϕ 130 ~ 133	250 W	ϕ 183 \times H90	DH.WHM121303	DH.WHM121313
2,000ml, ϕ 165 ~ 169	350 W	ϕ 220 \times H107	DH.WHM121304	DH.WHM121314
3,000ml, ϕ 184 ~ 187	490 W	ϕ 236 \times H210	DH.WHM121305	DH.WHM121315
4,000ml, ϕ 206 ~ 208	490 W	ϕ 260 \times H130	DH.WHM8117	DH.WHM8117.1
5,000ml, ϕ 221 ~ 224	600 W	ϕ 280 \times H140	DH.WHM121306	DH.WHM121316
10Lit, ϕ 278 ~ 282	850 W	ϕ 350 \times H170	DH.WHM121307	DH.WHM121317
20Lit, ϕ 344 ~ 348	1,500 W	ϕ 420 \times H210	DH.WHM121308	DH.WHM121318
50Lit, ϕ 489 ~ 494	2,000 W	ϕ 590 \times H290	DH.WHM8121	DH.WHM8121.1
100Lit, ϕ 609 ~ 614	2,000 W	ϕ 700 \times H340	DH.WHM8122	DH.WHM8122.1



Optional Remote Controller

- (a) Analog Remote Controller, 5~100% of Rated Voltage, Up to 1.2kW
 (b) Digital Remote Controller, Ambient +5 ~ 700°C,
 $\pm 1^\circ\text{C}$ Uniformity at Set Temp.

Cat. No.	
with 230V	with 120V
DH.WHM13500	DH.WHM23500
DH.WHM12500	DH.WHM22500