

IMPAC IPE 140/45

Addendum to IPE 140 Data Sheet

Special version of IPE 140 in a spectral range of the CO_2 absorption band.



The Impac® IPE 140/45 is a special pyrometer for the temperature measurement of hot, CO_2 containing combustion gas. The pyrometer is able to measure hot combustion gas (with typically approx. 10% CO_2) with a thickness of 40 cm.

Like the basic IPE 140, the IPE 140/45 is a highly accurate digital pyrometer. The narrow spectral range in the CO_2 absorption band enables the measurement of flames and hot combustion gases. For optimal match of the instrument to the application three different focusable optics are available.

PRODUCT HIGHLIGHTS

- Temperature range of 400 to 2000°C (752 to 3632°F)
- Measurement of flame temperatures
- Measurement of combustion gas temperatures

AT A GLANCE

Temperature Ranges

400 to 2000°C (752 to 3632°F) (MB 20)

Spectral Range

CO₂ absorption band for hot CO₂ gases

Optics

3 focusable optics

a = 115 to 170 mm

a = 210 to 500 mm

a = 360 to 10000 mm

REFERENCE NUMBERS

| IPE 140/45 | | | | |
|--------------------------------------|-----------------------|-------------|--|--|
| Temperature Range | Laser Targeting Light | View Finder | | |
| 400 to 2000°C (752 to 3632°F)(MB 20) | 3 875 880 | 3 875 890 | | |

TECHNICAL DATA¹

| Temperature Ranges | 400 to 2000°C (752 to 3632°F) (MB 20) |
|--|---|
| Spectral Range | CO ₂ absorption band for hot CO ₂ gas |
| Uncertainty $(T_{amb}=25^{\circ}C, \epsilon=1, t_{90}=1s)$ | < 1300°C: 0.6% of reading in °C |
| | > 1300°C: 0.8% of reading in °C |

¹ Different from IPE 140

OPTICS

| IPE 140/34 | | | | | |
|-----------------|---------------------------|------------------------------------|-------------------------|--|--|
| Optics | Manual Biston of and | Spot diameter M ₉₀ [mm] | | | |
| | Measuring Distance a [mm] | MB 20 | Objective Length S [mm] | | |
| 1-PE | 115 | 1.1 | 26 | | |
| | 135 | 1.3 | 13 | | |
| | 170 | 1.6 | 0 | | |
| 2-PE | 210 | 1.8 | 26 | | |
| | 280 | 2.6 | 13 | | |
| | 500 | 4.9 | 0 | | |
| 3-PE | 360 | 3 | 26 | | |
| | 625 | 5.6 | 13 | | |
| | 2000 | 20 | 4 | | |
| | 10,000 | 100 | 0 | | |
| Aperture D [mm] | | 14 to 17 | | | |



For international contact information, visit advancedenergy.com.

sales.support@aei.com +1 970 221 0108

PRECISION | POWER | PERFORMANCE

Specifications are subject to change without notice. Not responsible for errors or omissions. ©2019 Advanced Energy Industries, Inc. All rights reserved. Advanced Energy®, Impac®, and AE® are U.S. trademarks of Advanced Energy Industries, Inc.

