

## BAS 505 Precision WNB (605052000) Band Saw (220-240 V / 50 Hz); Cardboard box

Order no. 605052000 EAN 4007430207234



Product may differ from Image





- High precision and stability for highest cutting quality
- Two cutting speeds for various applications and materials
- Top and bottom HSS precision three-roller guide of the band saw blade for best cutting results, adjustable without tools
- Quiet induction motor, maintenance-free and robust.
- Restart protection: prevents unintentional start-up after power supply interruption
- Easy inclination adjustment of the grey cast iron saw table for precise incline cuts thanks to toothed ring guide
- Door opening without tools for easy saw blade change
- · Viewing window for blade clamp indicator for fast control of the blade clamping from outside
- Tool-less height adjustment of the saw blade guard
- Attachments can be stored in the saw housing
- External extraction possible for low-dust working
- Radius cutting with circle sawing attachment (accessory)

www.metabo.com 1/2



| Technical data               |  |
|------------------------------|--|
| Characteristics              |  |
| Dimensions                   | 834 x 639 x 1860 mm / 2.8 x 2.1 x 6.1 ft |
| Support surface              | 536 x 640 mm / 21 1/16 x 25 1/8 "        |
| Working height without stand | 925 mm / 36 1/2 "                        |
| Sawing bench swivel range    | 0 - 20 °                                 |
| Cutting height               | 280 mm / 11 "                            |
| Passage width                | 440 mm / 17 3/8 "                        |
| Cutting speed                | 430 m/min / 1020 m/min m/min             |
| Saw belt length              | 3380 mm / 133 "                          |
| Mains voltage                | 220 - 240 V                              |
| Rated input power            | 1500 W                                   |
| Output power                 | 1100 W                                   |
| Weight                       | 133 kg / 293 lbs                         |
| Noise emission               |  |
| Sound pressure level         | 82 dB(A)                                 |
| Sound power level (LwA)      | 90 dB(A)                                 |
| Uncertainty of measurement K | 4 dB(A)                                  |

## Scope of delivery

Universal band saw blade A6 Parallel Guide / Rip Fence Extraction nozzle (Ø 100 mm)

www.metabo.com 2 / 2