


Bath | circulation water bath

circulation water bath, 8 / 12 / 22 / 30 l, -25°C - +150°C ±0.1°C, 25 l/min, flat lid included



IQ | OQ
available

page 12 for details



Connection for external circulation Ø12.5mm

WCR -25°C - +150°C, digital

Ideal for:

- connection with evaporator

Features:

- stainless steel bath, polyurethane insulation of 40 mm thickness and body made of powder-coated steel
- innovated refrigeration system ensures temperature performance, includes intelligent control for preventing compressor overload, CFC-free (R-404A)
- innovated powerful circulation pump ensures temperature uniformity: internal and external circulation and 5 steps circulation speed
- stainless steel flat lid & valve ball included, dome lid optional
- RS232C interface: remote monitoring and controlling with PC
- proper liquid level tag in bath
- user's self-compensation function to control difference between real temperature and indicated temperature (±10.0°C)
- backlight LCD display
- CE certified and unique serial number for tracing

Safety mechanism:

- overheat and over-current protection
- sensor error detection and leakage breaker
- low liquid level warning and automatic stop function
- locking mode

Controller:

- digital fuzzy controller with **Jog-Dial-switch** (turn + push) & capacitive **touch button**

| Model | WCR-8 | WCR-12 | WCR-22 | WCR-30 |
|-------------------------------------|--|------------------------------|-------------------------------|-------------------------------|
| Capacity | 8 l | 12 l | 22 l | 30 l |
| Temperature range & accuracy | | -25°C - +150°C, ±0.1°C | | |
| Temperature resolution | | 0.1°C-display, 0.1°C-control | | |
| Temperature uniformity & probe | | ±0.2°C at -10°C, PT100 | | |
| Heating Power | 1.0 kW | 1.5 kW | 2 kW | 2.2 kW |
| External circulation nozzle | inner Ø10.5 mm, outer Ø12.5 mm, for inner circulating: connect directly the in-/outlet nozzles | | | |
| Pump | max. flow rate: 25l/min, max. pressure: 7.5 psi, max. lift: 4 m | | | |
| Refrigerator | 250 W | 250 W | 370 W | 560 W |
| Cooling capacity at +20°C | 300 W | 380 W | 680 W | 850 W |
| Cooling capacity at 0°C | 200 W | 250 W | 500 W | 620 W |
| Cooling capacity at -20°C | 110 W | 130 W | 300 W | 400 W |
| Timer & alarm | 99hr 59 min (delay & continuous run), error status & timer end | | | |
| Effective space | 175 x 153 x 150 mm | 230 x 181 x 150 mm | 290 x 220 x 200 mm | 330 x 290 x 200 mm |
| Internal dimensions (W x D x H, mm) | 175 x 320 x 150 mm | 230 x 350 x 150 mm | 290 x 390 x 200 mm | 330 x 460 x 200 mm |
| External dimensions (W x D x H, mm) | 330 x 474 x 752 mm | 400 x 523 x 807 mm | 483 x 563 x 850 mm | 494 x 633 x 906 mm |
| Packing size & gross weight | 560 x 420 x 922 mm, 45 kg | 630 x 530 x 972 mm, 54 kg | 670 x 615 x 1022 mm, 63 kg | 740 x 625 x 1072 mm, 70 kg |
| Power supply | 1 Phase AC 120V, 60 Hz or AC 230V, 50/60 Hz | | | |
| Order number 230V | DH.WCR00408 | DH.WCR00412 | DH.WCR00422 | DH.WCR00430 |
| Order number 120V | DH.WCR00508 | DH.WCR00512 | DH.WCR00522 | DH.WCR00530 |