


DAIHAN® Forced-air Drying Oven "ThermoStable™ OF", 3-Side Heating Zone, 50 · 105 · 155 · 305 Lit, up to 250℃, ±0.3℃ With Wire Shelves, Digital PID Control, Jog-Dial & Push Button, Digital LCD, with Back-light, Pre-Heating Zone, Certi. & Traceability

강제 순환식 정밀 건조기/오븐, 고정밀 디지털 퍼지 제어, 우수한 온도 정확성/균일성



(1) Standard Model, Forced-air Oven



3-Side Heating Zone Forced-air Mechanism :
The Best Temp. Uniformity & Accuracy by High Performance Heating Mechanism (Exclude OF-305, OF-W305)



Perfect Door Lock by Double Latch

- UL, CUL, and CE Certified(Exclude 305Lit-model) ■ GD(Good Design)-mark
- with Certificate & Traceability : Controlled by Serial Number, Certificate, Delivery-information, and Traceable Data Base System
- 3-Side Heating Zone : The Best Temp. Uniformity & Accuracy by High Performance Heating Mechanism
- Digital PID Control System Implementing Superior Temperature Accuracy
- Optimized Air Flow by Forced-air Mechanism
- Patented Jog-Dial Control System ■ PL(Prod uct Liability) Insurance
- * Suitable for Drying, Baking, Conditioning, Curing, Pre-Heating and Aging
- * Compact New Body Design * Alarm Function : Error status and Timer-end
- * RS232C Interface for Monitoring and Controlling with PC
- * Ambient +5℃ to 250℃ Range with Fluctuation of ±0.3℃ at 100℃
- * Locking Mode Supported for Experimental Safety (Input to Jog-Dial can be disabled)

Specification

Spec.		Model	(1) Standard Model			
			ThermoStable OF-50 Max. Capa. 50L	ThermoStable OF-105 Max. Capa. 105L	ThermoStable OF-155 Max. Capa. 155L	ThermoStable OF-305 Max. Capa. 305L
				(2) Window Model		
			ThermoStable OF-W105	ThermoStable OF-W155	ThermoStable OF-W305	
Capacity		50 Lit	105 Lit	155 Lit	305 Lit	
Dimension (w × d × h)	Interior (mm)	370 × 345 × 420	485 × 415 × 535	550 × 480 × 600	550 × 470 × 1,180	
	Exterior (mm)	518 × 647 × 724	653 × 712 × 882	718 × 777 × 947	721 × 777 × 1,619	
Heater Power		650 W	1.4 kW	1.6 kW	3.4 kW	
Temp.	Range	Room Temp +5°C to 250°C				
	Fluctuation	± 0.3°C at 100°C, ± 0.5°C at 150°C				
	Variation	± 1°C at 100°C, ± 1.8°C at 150°C				
	Sensor	PT 100				
Control Resolution		± 0.1°C				
Heat-up Time		25 min. to 100°C, 45 min. to 150°C		25 min. to 100°C, 40 min. to 150°C		
Recovery Time (Door open 30sec)		8 min. to 100°C, 8 min. to 150°C		6 min. to 100°C, 6 min. to 150°C		
Controller		Digital PID Control by Advanced Microprocessor Jog-Dial with Push Button				
RS232 Port		Available to connect with PC				
Display		Digital LCD with Back Light				
Timer		99hr 59 min (delay/continuous function)				
Storage		Temperature and Timer setting values				
Material	Internal	Stainless-steel (#304), Corrosion Resistant				
	External Insulation	Powder Coated steel Glass Wool				
Shelf (included)		2 Wire Shelf		3 Wire Shelf		
		Load per Stainless-steel Wire Shelf : 16 kg				
Ventilation		Ventilation hole with Stainless-steel Cap, Hole Diameter 40mm				
		1ea	2ea	3ea		
Circulation		Forced-air Type				
Safety device		Over Temp. and Over Current Protector, Sensor Error Detector				
Alarm		Error Status and Timer-end				
Net Weight (kg)		44	69	78	159	
Packing Size (w × d × h)(mm)		622 × 754 × 807	743 × 819 × 1,068	808 × 884 × 1,133	1,000 × 1,000 × 1,870	
Shipping Weight (kg)		59	79	92	219	
Power Consumption		674 W	1390 W	1566 W	3200 W	
Energy Consumption, at 100°C		117 Wh	187 Wh	204 Wh	-	
	, at 150°C	230 Wh	337 Wh	398 Wh	-	
Electric Reqts.		120V, 60Hz or 230V, 50/60Hz				

* Other Specifications are available upon Customer's Request.

Ordering Information

(1) Standard Model, Forced-air, with Wire Shelf

DH.WOF05050	Oven, Standard, 230V, 50 Lit, "ThermoStable OF-50"
DH.WOF05105	, 105 Lit, "ThermoStable OF-105"
DH.WOF05155	, 155 Lit, "ThermoStable OF-155"
DH.WOF05305	, 305 Lit, "ThermoStable OF-305"
DH.WOF06050	Oven, Standard, 120V, 50 Lit, "ThermoStable OF-50"
DH.WOF06105	, 105 Lit, "ThermoStable OF-105"
DH.WOF06155	, 155 Lit, "ThermoStable OF-155"
DH.WOF06305	, 305 Lit, "ThermoStable OF-305"

(2) Built in Viewing Window Model, Forced-air, with Wire Shelf

DH.WOF07105	Oven, Window, 230V, 105 Lit, "ThermoStable OF-W105"
DH.WOF07155	, 155 Lit, "ThermoStable OF-W155"
DH.WOF07305	, 305 Lit, "ThermoStable OF-W305"
DH.WOF08105	Oven, Window, 120V, 105 Lit, "ThermoStable OF-W105"
DH.WOF08155	, 155 Lit, "ThermoStable OF-W155"
DH.WOF08305	, 305 Lit, "ThermoStable OF-W305"


Spare Stainless-steel Wire Shelf

DH.WOF11050	Wire Shelf, for 50 Lit, "OFS050", w340×d310mm
DH.WOF11105	, for 105 Lit, "OFS105", w455×d375mm
DH.WOF11155	, for 155-305-Lit, "OFS155", w520×d440mm

Forced-air Oven with Validation (IQ, OQ) Service

DH.WOF31050	Validation Service(IQ, OQ), with "ThermoStable OF-50", "OFV1050"
DH.WOF31105	Validation Service(IQ, OQ), with "ThermoStable OF-105", "OFV1105"
DH.WOF31155	Validation Service(IQ, OQ), with "ThermoStable OF-155", "OFV1155"
DH.WOF32105	Validation Service(IQ, OQ), with "ThermoStable OF-W105", "OFV2105"
DH.WOF32155	Validation Service(IQ, OQ), with "ThermoStable OF-W155", "OFV2155"


>> New Jog-Dial Controller



- Provides the user interface with an ergonomic design for users to operate in an easy and convenient way.
- A new 2-way Jog-Dial Knob (Jog Dial + Push Button) and presents excellent durability and mobility.
- High-quality LCD with Back-light function.
- A durable Main Button and a Sub Button that features superb and user-friendly operation.



(2) Window Model, Forced-air Oven



Stainless-steel Wire Shelf (Included)



WiseRemote Control Software :
Connection of Temperature Devices with Interface RS232C to a PC Export Recorded Data(Excel Spreadsheet)

* You can Download this Software at
DAIHAN-Sci.com Shopping-mall