

**XIAMEN TOB NEW ENERGY TECHNOLOGY CO., LTD.**

Provide A Full Set Of Solutions For Battery Machines.

SALES tob.amy@tobmachine.com

TECH SUPPORT +86-18120715609

Search...



## DHG-9070A 70L Blast Drying Oven



The TOB-DHG-9070A Blast Drying Oven is mainly used For scientific research units, specialty universities, laboratories, industrial mining enterprises etc and production field for materials drying and heat treatment.

- Item No.:TOB-DHG-9070A
- Order(Moq):1
- Payment:L/C,T/T,Western Union, Paypal
- Product Origin:China
- Shipping Port:XIAMEN
- Lead Time:7

## Product Detail

### 70L, 2.5 Cubic Feet Blast Drying Oven with 30 Segments Temperature Controller Optional

#### SPECIFICATIONS

- 1 The TOB-DHG-9070A Blast Drying Oven is mainly used For scientific research units, specialty universities, laboratories, industrial mining enterprises etc and production field for materials drying and heat treatment.
- 2 This Forced air drying oven adopts high quality cold rolled steel sheet, with strong rust resistance. The inner material is stainless steel, easy cleaning.
- 3 Reasonable hot air circulation channel is designed in the cabinet, so that the temperature distribution in the cabinet is more even, temperature rise faster. Equipped with adjustable air outlet, for adjusting the in and out of the air in the cabinet. And also can output the bad air with connecting a pipe outside work place.

4 Temperature control is microcomputer intelligent digital technology controller with PID function and LED display.

5 The 30 segment programmable temperature controller is with time and temperature setting in sectional with sound alarm.

Model	Blast Drying Oven TOB-DHG-9070A
Source voltage	110V/220V 50HZ/60HZ
Power	1500W
Warranty	One Year limited warranty with lifetime support
Work box size	400*350*500mm
Oven size	545*545*800mm
Temperature range	RT+10~250°C
Temperature resolution	±0.1°C
Temperature fluctuation	±0.5°C
Temperature controller	30 segment programmable temperature controller. Self tuning function. The timing time can up to 9999 minutes
Inner box material	High quality mirror stainless steel plate, round shape, smooth surface, easy to clean
Outside material	High quality cold-rolled steel plate, the surface electrostatic spray, hard and firm coat, with strong anti rust ability
Sensor	A grade PT100 Platinum resistance
Heat pressure layer	High quality insulation system, inner box, inner shell, ultra-fine glass fiber, Aluminum foil aluminum reflector, air - interlayer from inside to outside.
Observe window	The box door are provided with double-layer tempered glass observation window, can observe the test result easily
Heating mode	Electric heating. Nickel chromium alloy electric heater

Safety installation	With over temperature protection, grounding etc.
Wind duct	Forced air circulation channel, ensure that the studio uniform temperature; air duct provided with a heater, temperature sensor
Adjustable air intake	The control box and outlet air quantity, the casing is provided with an exhaust  can close or adjust discharge mouth to change wind effect.
Shelf	2pcs
Timing range	1-9999mins

## PRODUCT DISPLAY



## SERVICES

- 1 We supply machines with battery technology support.
- 2 We can also supply a full set of materials for lithium battery including polymer battery, cylinder battery, mobile phone battery, EV battery.
- 3 We can also supply a full set of lithium battery equipment for lab research, pilot scale research and production line.
- 4 We can also supply a full set of battery technology for battery design, research and producing.

