

Search...





SALES tob.amy@tobmachine.com









XIAMEN TOB NEW ENERGY TECHNOLOGY CO., LTD.

Provide A Full Set Of Solutions For Battery Machines.

TECH SUPPORT +86-18120715609



Laboratory Digital Display Viscometer 10-200000cp

This edge hotting machine is used for lithium pouch cell/Lithium polymer cell Edge hot shaping after edge folding.

- Item No.:TOB-SNB-1A
- Order(Moq):1set
- Payment:L/C,T/T,Western Union, Paypal
- Product Origin: China
- Shipping Port:XIAMEN
- Lead Time:7days

Product Detail

Laboratory Digital Viscometer 10-200000cp Viscosity Testing Equipment

SPECIFICATIONS

The SNB-1ADigital display viscometeris widely used in solvent based adhesive, latex, biochemical products, cosmetics, paint, paint, ink, paper pulp, food, starch and other industries.

Thisviscometerhas testing range of 10-200000cp, with small quantity sample of 18-20ml, it testing result can directly displayed on the digital screen without any calculating. English digital display is easy understand, it is with RS232 interface, can be connect with computer for date output.

Model	Digital display viscometer TOB-SNB-1A
Measuring range	10-200000cp
Sample quantity	20 ml
Measuring accuracy	±1%
(Newtonian liquid)	
Standard rotor specification	21#/27#/28#/29# rotors
Rotation rate (RPM/min)	0.5/1/2/5/10/20/50
Dimension	300*300*450mm
Net weight	2kg (not including pedestal)
Package weight	7.4kg
Package size	480*250*400mm
Working temperature	5-35°C
Working humidity	≤80%
Source voltage	AC 100-230V 45-65HZ

STANDARD PACKAGE LIST

Item	Qty
Digital display viscometer	1 set
Power line (according to your requirements)	1 pcs
Standard rotor 21#/27#/28#/29#	Total 4 pcs
Operating manual (English)	1 book

PRODUCT DISPLAY

















COMPANY CERTIFICATE







CE CERTIFICATE



















