



XIAMEN TOB NEW ENERGY TECHNOLOGY CO., LTD.

Provide A Full Set Of Solutions For Battery Machines.

SALES tob.amy@tobmachine.com

TECH SUPPORT +86-18120715609

Search..



300mm Width Roll To Roll Pressure Adjust Rolling Press Machine



TOB-HP-300C Hydraulic Roller pressure machine is an Automatic Battery Electrode Rolling Press System with precision digital pressure control . The pressure can be adjusted easily by touch screen. It biggest roller press width is 300mm.

- Item No.:TOB-HP-300C
- Order(Moq):1set
- Payment:L/C,T/T,Western Union, Paypal
- Product Origin:China
- Shipping Port:XIAMEN
- Lead Time:7days

Product Detail

300mm width Roll to Roll Pressure Adjust Rolling Press Machine for Battery Electrodes

SPECIFICATIONS

1 TOB-HP-300 Hydraulic Roller pressure machine is an Automatic Battery Electrode Rolling Press System with precision digital pressure control . The pressure can be adjusted easily by touch screen. Its biggest roller press width is 300mm.

2 It is with tension controlled feeding and winding devices with the electric rolling press machine, which can roll to roll continuous Electrode calendaring, suitable for battery electrode roll to roll calendaring for pilot scale research work.

3 You can also just choose the hydraulic roller press machine without feeding and winding device as model TOB-HP-300 Or you can also add heat function to this roller press machine with Temperature up to 130C as model TOB-HP-300T or TOB-HP-300TC with winding and feeding as continuous model..

Model	Roll to Roll Pressure Adjust Rolling Press Machine TOB-HP-300C
Function	Calender battery electrode
Calender Thickness	0.01-3mm adjusted
Calender Width	Max 300mm
Calender Pressure	Max 20KN
Speed	1-3m/min
Working Roller	Diameter 210mm, 9Cr3Mo materials
Roller Width	300mm
Calender Model	Hydraulic press
Accuracy	0.003mm
Rolling Press Machine Power	1.5KW
Winding and Unwinding power	0.55KW
Tension Control	Absolute value photoelectric encoder with floating guide roller
Rolling Press Machine Size	About L1300mm*W600mm*H1300mm
Total Installation Dimension	L3000mm*W1200mm*H1300mm
Power Supply	380V 4KW

Electric control

With tension display, rolling speed display function

Electric motor revolution and counter revolution

PRODUCT DISPLAY







PACKAGE

