



**XIAMEN TOB NEW ENERGY TECHNOLOGY CO., LTD.**

Provide A Full Set Of Solutions For Battery Machines.

SALES tob.amy@tobmachine.com

TECH SUPPORT +86-18120715609

Search...



## Single Head Electric Injection Pump For Electrolyte



### Single Head Electric Injection Pump For Electrolyte

- Item No.:TOB-D1876
- Order(Moq):1set
- Payment:L/C,T/T,Western Union, Paypal
- Product Origin:China
- Shipping Port:XIAMEN
- Lead Time:7days
- 
- Lead Time:7days

## Product Detail

**Single Head Electric Injection Pump Used For Battery Electrolyte, Capacitor, Acid, Alkali, Glue, Reagents, and Other Industries Liquid Injection**

## SPECIFICATIONS

**1 TOB-D1876 Single Head Electric Injection Pump** is mainly used for the battery electrolyte, capacitor, acid, alkali, glue, reagents, and other industries of high precision fluid metering injection liquid

**2 This ceramic pump** has high safety performance with Password protection and factory restore function to ensure setting parameters can not be changed arbitrarily.

Model	Single Head Electric Injection Pump TOB-D1876
Warranty	One year limited and lifetime support
Type	Rotating reciprocating positive displacement special ceramic injection pump
Speed (r/min)	18-1000, According to system configuration and fluid characteristics
Stroke number	1-10000times, According to system configuration and fluid characteristics
Ceramic Pump	
Materials	Using nanotechnology and gel injection molding processing and molding technology,  the microstructure uniformity, high density
Pump core technology	High precision polishing processing, do not need to seal and lubricating oil
Pump core performance	High temperature resistance, wear resistance, acid and alkali resistance,  high hardness and low coefficient of friction
Capacity range	Single pump, 0-1876ul, Max0-1876 microlitre/one stroke
Ceramic pump sleeve	SUS316 stainless steel
Filling accuracy	Within 5‰
Import and export pipeline	Standard  (liquid into the tube diameter 6 mm, outside diameter of 8 mm, tube inner diameter 4 mm, outside diameter 6 mm)
Dimension	270*120mm*145mm (L*W*H)

Weight	About 2.8kg
Controller Box	
Source voltage	AC110V/220V, 50/60HZ Single phase
Power	200W
Dimension	290*210*145mm (L*W*H)
Weight	4.3kg
Standard interface	I/O, RS232, CC TRIG, AUX OUT (optional pedal)
Safety performance	Password protection and factory restore function to ensure setting parameters can not be changed arbitrarily

## PRODUCT DISPLAY

### Electric Injection Pump with control box



### Electric Priming Pump filling process

