



XIAMEN TOB NEW ENERGY TECHNOLOGY CO., LTD.

Provide A Full Set Of Solutions For Battery Machines.

SALES tob.amy@tobmachine.com

TECH SUPPORT +86-18120715609

Search...



Two Station Top-Side Sealing Machine For Pouch Cell



Two Station Top-side Sealing Machine For Pouch Cell

- Brand:TOB NEW ENERGY
- Item No.:TOB-MY-06-200-2
- Order(Moq):1set
- Payment:L/C,T/T,Western Union, Paypal
- Product Origin:China
- Shipping Port:XIAMEN
- Lead Time:30days

Product Detail

200mm Sealing Head Lithium Battery Aluminum Film Cup Top-side Sealing

SPECIFICATIONS

- 1.TOB-MY-06-200-2 Two station sealing machine is used for lithium polymer battery pouch top and side heat sealing before electrolyte filled.
- 2.Can pre-set sealing temperature and sealing time.
- 3.Temperature lower and higher alarm function.
- 4.Without battery missing sealing or repeat sealing.
- 5.With light curtain safety protection and back door switch protection.
- 6.With our-put statistics function.
- 7.Adopt programmable controller PLC to realize automatic control, touch screen man-machine conversation, convenient operation and setting.

Working process:

Polymer Battery into fixture, Battery feeding-top sealing position-side sealing position-battery discharge, Finish battery top and side heat seal.

Model	TOB-MY-06-200-2
Type	Two work station
Source voltage	AC 110V/220V, 50/60HZ
Power	1200W
Warranty	One year limited warranty with lifetime support
Air compression	≥0.6MPa
Size (L*W*H)	540*640*1450mm
Sealing head length	200mm
Suitable battery size	≤180*120*8mm
Sealing stamp width	2-10mm, Top sealing : 4mm, Side sealing : 6mm (customized)
Sealing thickness	0.19-0.3mm
Sealing temperature	RT-260°C adjustable, Accuracy ±3°
Sealing time	0-99.9s, adjustable
Feed accuracy	±0.05mm
Output	400-600 Times/H
Shelter height	4mm, Sealing battery thickness : 2-10mm