MEDSOURCE DESKTOP STEAM STERILIZER

YLT-230A YLT-250A YLT-255A YLT-310A



ISO13485, and GMP.



MEDSOURCE DESKTOP STEAM STERILIZER

Function Features:

- 1. The housing of the sterilizer is composed of upper lid coated with baking enamel, and lower lid covered by stainless steel for protection. It has advantages of corrosion resistance, cleaning convenience and aesthetics, etc.
- 2. It's an automatic controlled process including heating up, sterilization, steam exhaust and drying, and its operation process will be displayed by the control panel.
- 3. Control parts including: temperature adjuster, sterilization timer, drying timer, pressure gauge, water inlet and water drainage device, these can all be operated and monitored at the front of the stand.
- 4. The integrated door cover is made of PC synthetic plastic materials, with advanced and aesthetic spiral T-handler made of special steel. It has the advantages of simple and convenient operation, high safety, meet ergonomic principles, and long life cycle etc.
- Exhaust valve of heavy mallet type can make sterilization and dry function more perfect.
- 6. The international standard design of safety valve will take action immediately when the pressure of inner chamber exceeds the 10% of max, usage pressure value, which meets the pressure capacity safety regulation.
- Quality standard: certification of ISO9001, ISO13485, and GMP.
- 8. Safety devices: Pressure control switch, Safety relief valve, Over heat protection switch, operative switch upon door closed, safty door lock device Specification

| Functions Model | YLT-230A | YLT-250A | YLT-255A | YLT-310A |
|-------------------------------|--|---|--|--|
| Outline Dimension (cm) | W47cm x D61cm x H39cm | W48cm x D61cm x H39cm | W48cm x D73cm x H39cm | W57cm x D76cm x H43 cm |
| Pot Dimension (cm) | Ø23cm x D40 cm | Ø25cm x D41 cm | Ø25cm x D50 cm | Ø31cm x D56 cm |
| Pot Volume (litre) | 16L | 20L | 24L | 42L |
| Rated Power | inner chamber heater 1300W Dry Heater Piece 300W | inner chamber heater 1 450W Dry Heater Piece 300W | inner chamber heater 1800W Dry Heater Piece 300W | inner chamber heater 2000W Dry Heater Piece 300V |
| Rated Current | 230AC 1phase 8.3Amp | 230AC 1phase 9.1Amp | 230AC 1phase 11Amp | 230AC 1phase 13Amp |
| Water Tank Capacity (L) | 5L | 5L | 5L | 8L |
| Net Weight (Kg) | 35 Kg | 39 Kg | 46 Kg | 60 Kg |
| Sterilization Temperature | 121~134°C | 121~134°C | 121~134°C | 121~134°C |
| Designed Pressure (kg/cm²) | Max 2.5kg/cm² | Max 2.5kg/cm² | Max 2.5kg/cm² | Max 2.5kg/cm² |
| Accessories | 1 of Stainless steel Tray Disinfection box X 1pc | 1 of Stainless steel Tray Disinfection box X 1pc | 1 of Stainless steel Tray Disinfection box X 1pc | 1 of Stainless steel Tra- Disinfection box X 1pc |



No. 32-12,Lane 320, Sec 1,shatian Rd., Dadu E-MAIL: tc.taichang@msa.hinet.net

www.medsource.com.tw