

0.05-0.12mm Ni Tab Spot Welder For Batteries



Ni Tab Spot Welder Machine For Lithium Ion Battery

- Item No.:TOB-HT-012
- Order(Moq):1set
- Payment:L/C,T/T,Western Union, Paypal
- Product Origin:China
- Shipping Port:XIAMEN
- Lead Time:7days

Product Detail

Double Point DC Spot Welder For Batteries Ni Tab Thickness 0.05-0.12mm, 110V-240V Customized

SPECIFICATIONS

1 TOB-HT-012 Model Spot Welder For Batteries has two kinds type to choose, pneumatic spot welding machine with smaller shipping weight and volume, but need to connect air compressor. Pedal Type spot welding machine without air supply but need with desk shipping together.

2 This kind battery spot welder is mainly used for 18650, 26650, 32650 cylindrical battery, NI-MH battery (nickel-metal hydride battery), Nickel cadmium battery and EV Lithium battery pack Ni tab welding.

3 TOB-HT System battery spot welder machine has different models according to its welding ability. TOB-HT-012 Spot welder is suitable for Ni tab thickness less than 0.12mm, TOB-HT-015 model suitable for Ni tab thickness less than 0.15mm. TOB-HT-022 model suitable for Ni tab less than 0.22mm. We can also supply high power spot welding machine can weld up to 1mm tab. Please contact with our engineers to get the most suitable machines for you.

Model	Spot Welder For Batteries TOB-HT-012
Source voltage	110V-240V with transformer, Single Phase 50/60Hz
Power	10KVA
Welding ability	0.05-0.12mm Ni tab
Warranty	One year limited and lifetime support
Advantages	<p>1 Double pulse welding - pre welding and welding</p> <p>2 Microcomputer control precision, Guarantee the evenness of each welding effect</p> <p>3 Automatic count</p>
Scope of application	<p>18650, 26650, 32650 cylindrical battery, NI-MH battery (nickel-metal hydride battery), Nickel cadmium battery and EV Lithium battery pack Ni tab welding</p>
Welding setting	<p>Pre welding current : 00-99A,</p> <p>Welding time : 00-30S</p> <p>Welding current : 00-99A</p>
Welding stroke	25mm, the welding height can be adjusted
Operating	Foot switch and pneumatic model can be chosen
Control	<p>The microcomputer chip control,</p> <p>LCD liquid crystal display, simple and precision</p>
Weight	50kg

Dimension (L*W*H)	Foot switch model with desk : 800*580*1100mm Pneumatic model : 400*370*220mm
----------------------	---

PRODUCT DISPLAY



PACKAGE AND SHIPPING

- 1 Standard exported package : Internal anticollision protection, external export wooden box package
- 2 Shipping by express, by air, by sea according to customer's requirements to suggest the most suitable shipping mode
- 3 Responsible for the damage during shipping process, change the damage part for free
- 4 Supply with suitable voltage input and power plug according to customer's country requirements.
- 5 Supply with CO, ECO, FORM A, FORM E and any other original certificate for import custom clearance and tax relief.

SERVICES

- 1 We supply machines with battery technology support.
- 2 We can also supply a full set of materials for lithium battery including polymer battery, cylinder battery, mobile phone battery, EV battery.
- 3 We can also supply a full set of lithium battery equipment for lab research, pilot scale research and production line.
- 4 We can also supply a full set of battery technology for battery design, research and producing.