





TOB-ZDJ-5 type automatic titrator is a kind of high precision laboratory analysis instruments.

- Item No.:TOB-ZDJ-5
- Order(Moq):1 set
- Payment:L/C,T/T,Western Union
- Product Origin: China
- Shipping Port:XIAMEN
- Lead Time:7 days

## **Product Detail**

**Automatic Potentiometric Titration For Concentration Measuring** Instrument

## **SPECIFICATIONS**

TOB-ZDJ-5 type automatic titrator is a kind of high precision laboratory analysis instruments, it is mainly used in institutions of higher learning, scientific research institution, petrochemical industry, pharmacy, drug testing, metallurgical and other industries of chemical analysis of various kinds of ingredients.

| Model                                | Automatic Potentiometric Titration TOB-ZDJ-5    |
|--------------------------------------|---|
| Voltage source                       | AC110V/220V, 50/60HZ                            |
| Power                                | 50W   |
| Warranty                             | One year limited warranty with lifetime support |
| Testing range                        | pH: (0.00~14.00)pH                              |
|                                      | mV: (-1999.0~1999.0)mV                          |
|                                      | TEM : (-5.0~105.0)°C                            |
| Resolution                           | Ph: 0.01pH                                      |
|                                      | mV: 0.1mV                                       |
|                                      | TEM : 0.1°C                                     |
| Electronic unit basic error          | Ph: ±0.01pH±1                                   |
|                                      | mV: ±0.03%                                      |
|                                      | TEM : ±0.3°C                                    |
|                                      | Control titration sensitivity : ±2mV            |
| Burette capacity tolerance           | 10ml burette: ±0.025ml                          |
|                                      | 20ml burette: ±0.035ml                          |
| Burette infusion or rehydration rate | 55±10s  |
| Test repeatability                   | 0.2%  |
| Operating temperature                | (5.0~35.0) °C                                   |
| Working humidity                     | ≤80%  |
| Dimension(L*W*H)                     | 360*300*300mm                                   |
| Weight                               | 10kg  |

## PACKAGE AND SHIPPING

- 1 Standard exported package: Internal anticollision protection, external export wooden box package
- 2 Shipping by express, by air, by sea according to customer's requirements to suggest the most suitable shipping mode
- 3 Responsible for the damage during shipping process, change the damage part for free
- 4 Supply with suitable voltage input and power plug according to customer's country requirements.
- 5 Supply with CO, ECO, FORM A, FORM E and any other original certificate for import custom clearance and tax relief.

## SERVICES

- 1 We supply machines with battery technology support.
- 2 We can also supply a full set of materials for lithium battery including polymer battery, cylinder battery, mobile phone battery, EV battery.
- 3 We can also supply a full set of lithium battery equipment for lab research, pilot scale research and production line.
- 4 We can also supply a full set of battery technology for battery design, research and producing.

We cooperated with each other, and we will do TOP OF THE BEST battery