

Search...

Q

1200 °C Single-Temperature Zone Rapid Heating Furnace

1200 °C single-temperature zone rapid heating furnace

- Brand:TOB NEW ENERGY
- Item No.:TOB-DSP-1200°C-SZ
- Order(Moq):1set
- Payment:L/C,T/T,Western Union, Paypal
- Product Origin:China
- Shipping Port:XIAMEN
- Lead Time:7days



Product Detail 1200 °C single-temperature zone rapid heating furnace

SPECIFICATIONS

Model	TOB-DSP-1200°C-SZI	TOB-DSP-1200°C-SZII	TOB-DSP-1200°C-SZIII	
Power	2.5 KW	3.5 KW	3.5 KW	
Furnace tube size(mm)	Dia 60(OD) X1460 mm	Dia80(OD)X1460	Dia100(OD)X1460	
Dimension	1500X490X600	1500X490X600	1500X490X600	
Power supply voltage	220V			
Phase number	Single-phase			
Control mode	Yudian temperature control			
	30 sections can only use PID temperature regulation.			
	FP93 temperature control (from Japan)			
	(Replace imported instruments, for an additional fee)			
	1,40 section program temperature control can be divided into 4,2,1 group program,			
	if the program is divided into four groups, each program segment 10,			
	2,6 group PID control, low, medium and high temperature can each with a set of PID,			
	such that each segment is capable of controlling the temperature is very accurate.			
Control accuracy	+/- 1 °C			
Trigger	Phase-shift trigger			
SCR	106 / 16E Germany Simon Kang			
Max temperature	1200 °C			
Rated temperature	1100 °C			
Heating rate	≤30 °C/ Min (Available upon request modification)			
Recommended heating rate	≤100°C/ Min			

Heating length	400mm
Thermostatic length	150mm
Thermocouple Type	K type
Surrounding surface temperature	≤45°C
Security System	With the furnace air switch and fuse, when the current exceeds the rated current, it will automatically jump open, effective protection electric stove.



Furnace material:Polycrystalline alumina fibers (Alumina content of more than 95%) imported from Japan



TOB-DSP-VSHigh vacuum system

03

Heating element: Swedish import resistance wire Kanthal A1



