



## WH-1540 Four Station Soldering Machine



## Feature:

- 4 station jobs: soldering, fluxing, dipping (cleaning), unloading.
- 7 days pre-heating, 6 section ON / OFF control per day to save the waiting time.
- Electric control & heating apparatus is independent to offer the safety control mode.
- Detective sensor of temperature to prevent the machine action error.
- Digital temperature control to have precise temperature control (tolerance range +3% to -1%)
- Pure titanium tank for lead free solder.
- Pure titanium tank for longer life of solder pot.
- Jig holder for several coils for economic benefit.

- With output calculate function to confirm the finished amount.
- 999 memories of program to save the setting time.
- Each data has 4 stroke setting & 2 delay time control for various soldering mode.
- Pitch accuracy can reach 0.025mm, most stable for product soldering.
- Provide reliable working environment with safety protection device.
- Tin residue collection box is convenient to clean.
- Smokestack device to prevent operator smell the pernicious gases. Easy to operate with various function.

## **Specification:**

| Power Source        | AC 220V                             |
|---------------------|-------------------------------------|
| Air Pressure        | 5Kg / cm (white wire is earth wire) |
| Exhaust Fan Size    | 4"                                  |
| Solder Pot Size     | 160 x 120 x 90 mm                   |
| Heater              | 700W x 2 / AC 220V                  |
| Solder width        | 123 mm                              |
| Temperature control | Room temperature ~ 500°C            |
| Machine Dimension   | 1066 x 715 x 1360 mm                |
| Machine Weight      | 120 KGS                             |

BACK