



## DT-8865

8665 Infrared Temperature Finder is visible for higher/lower temperature. It permits targeted scanning to find higher/lower temperature with continuous audible alarm. It provides faster sampling time and higher accuracy, widely applicant in industrial and environment field.



-Targeted scanning for higher/lower temperature

-The position of higher/lower temperature can be precisely found.

-Enables you to work with certainty for Fault diagnosis

-The Audible will alarm when temperature is changed with switchable audible of higher/lower temperature

-LCD display with new target graphics

-Easy keypad operatio

<b>Features</b>	
T-Sound: Changeable beeper indication by Temperature	
User selectable °C or °F	
Dual laser targeting	
Automatic Data Hold	
Auto Power Off	
White Backlit LCD Display	
Overrange indication	
Trigger lock for continuous use	
Max/Min display	
20:1 distance to target ratio measures smaller surface areas at greater distances	
Green, Red & Blue backlight: Normal, Higher & Lower temperature indications	

<b>Specifications</b>	
IR Temp. Range	-50°C to 380°C -58°F to 716°F
IR Temp. Resolution	0.1°
Emissivity	Fixed at 0.95
Temp. Basic Accuracy	±1.0% of reading
Response Time	Less than 150ms
Spectral Response	8-14µm

Applications  
Cooling and Reheating  
Serving areas  
Food service Equipment  
Cold storage

Accessories: 9V battery, Carrying case and Gift box.