



IR-66/66B

Series Pocket IR Thermometers

User selectable; Automatic Data Hold; Auto Power Off; Low battery indication; Lock function; Set Min, Max; Fast sampling time; <1s, 300ms; High accuracy: 1.50%



Features	IR-66	IR-66B
User selectable	*	*
Automatic Data Hold	*	*
Auto Power Off	*	*
Low battery indication	*	*
Lock function	*	*
Set Min, Max	*	*
Fast sampling time	<1s	300ms
High accuracy		1.50%

Size(HxWxD): 75mm x 40mm x 20mm

Weight: 33g

Specifications	IR-66	IR-68
Range	-35°C to 230°C/B17 -31°F to 446°F	-35°C to 250°C/ -31°F to 482°F
Response Time	Less than 1s	Less than 300ms
Basic Accuracy	±2.0% of reading or ±2°C/±4°F	±1.5% of reading or ±2°C/±4°F
Optical Resolution	1:1	
Resolution	0.1°C/°F	
Emissivity	Fixed at 0.95	
Size (H*W*D)	75mm*40mm*20mm	
Weight	33g	

Applications



Series Pocket IR Thermometers

User selectable; Automatic Data Hold; Auto Power Off; Low battery indication; Lock function; Set Min, Max; Fast sampling time; <1s, 300ms; High accuracy: 1.50%

1.5% Accuracy (IR-66B)

300ms faster sampling time (IR-66B)

Accessories : One CR2032 button battery, Carrying Case & Clamshell