



DT-9560/9561/956

2

Heavy Duty Industrial Digital
Multimeters with VFD Measurement



Features	9560	9561	9562
Low pass filter for accurate measurement of Variable frequency drive(VFD) signal	*	*	*
Display Count with LED Backlight	4000	4000	6000
Auto Range & Auto Power Off	*	*	*
True RMS	*	*	*
AC Bandwidth(Hz)	50Hz-400Hz	50Hz-400Hz	50Hz-400Hz
Continuity Buzzer & Diode	*	*	*
Low Battery Indication	*	*	*
Data Hold ,MAX/MIN & Relative Mode	*	*	*
Analogue Bar Graph			41
Input Protection	*	*	*
IP67 Waterproof	*	*	*

Size(HxWxD): 180mm x 82mm x 55mm

Weight: 255g

Specifications				
		Best Accuracy		
Model	Range	9560	9561	9562
DC Voltage(V)	600mV/6V/60V/600V/1000V			±(0.8%+1)
	400mV/4V/40V/400V/1000V	±(0.8%+1)	±(0.8%+1)	
AC Voltage(V)	600mV/6V/60V/600V/1000V			±(1%+3)
	400mV/4V/40V/400V/1000V	±(1%+3)	±(1%+3)	
DC Voltage(A)	600μA/6000μA/60mA/600mA/6A/10A			±(1%+3)
	400μA/4000μA/40mA/400mA/4A/10A	±(1%+3)	±(1%+3)	
AC Current(A)	600μA/6000μA/60mA/600mA/6A/10A			±(1.2%+5)
	400μA/4000μA/40mA/400mA/4A/10A	±(1.2%+5)	±(1.2%+5)	
Resistance (Ω)	600Ω/6KΩ/60KΩ/600KΩ/6MΩ/60MΩ			±(2%+2)
	400Ω/4KΩ/40KΩ/400KΩ/4MΩ/40MΩ	±(2%+2)	±(2%+2)	
Capacitance(F)	40nF/400nF/4μF/40μF/400μF/4000μF	±(3%+5)	±(3%+5)	±(3%+5)
	40nF/400nF/4μF/40μF/400μF/4mF/40mF			
Frequency(Hz)	10Hz-10MHz	±(1.5%+5)	±(1.5%+5)	±(1.5%+5)
Temperature (°C)	-45°C~1000°C		±(3.0%+5)	±(3.0%+5)
Temperature (F)	-50°F~1382°F		±(3.0%+9)	±(3.0%+9)

Accessories: Test leads, 9V battery and gift box with carrying case.

