



## DT-9915H/9917H/9918T

They set the standard with a combination of precision, features, easy-to-use, safety and reliability.

Have True RMS AC Voltage, Current readings, as well as Frequency and Capacitance ranges.

### Safety Conformance

- EN61010-1 CAT IV 600V, CAT III 1000V
- 1000V input protection on all ranges
- 10A/1000V & 0.5A/1000V fuses
- protection on current ranges



<b>Features</b>			
	<b>9915H</b>	<b>9917H</b>	<b>9918T</b>
<b>Digital LCD display counts</b>	<b>6000</b>	<b>6000</b>	<b>6000</b>
<b>True RMS measurement</b>	*	*	*
<b>Temperature measurement</b>		*	*
<b>IP67 &amp; Safety design</b>	*	*	*
<b>Relative zero</b>	*	*	
<b>Wide capacitance range</b>	*	*	*
<b>Max/Min recording mode &amp; Data Hold</b>	*	*	*
<b>Auto Power Off &amp; Backlight</b>	*	*	*
<b>AC/DC current clamp-on adaptor input</b>	*	*	
<b>Peak capture mode</b>			*
<b>Analog bargraph/segment</b>			*

<b>Specifications</b>					
<b>Function</b>	<b>Max. Range</b>	<b>Basic Accuracy</b>	<b>9915H</b>	<b>9917H</b>	<b>9918T</b>
<b>Voltage DC</b>	<b>1000 V</b>	<b>±0.5%+5digits</b>	*	*	*
<b>Voltage AC</b>	<b>1000V</b>	<b>±0.8%+3digits</b>	*	*	*
<b>Current DC</b>	<b>10A</b>	<b>±1.0%+3digits</b>	*	*	*
<b>Current AC</b>	<b>10A</b>	<b>±1.5%+3digits</b>	*	*	*
<b>Resistance</b>	<b>60MΩ</b>	<b>±0.8%+2digits</b>	*	*	*
<b>Duty Cycle</b>	<b>99.9%</b>	<b>±1.2%+2digits</b>	*	*	*
<b>Frequency</b>	<b>9.999MHz</b>	<b>±1.0%+5digits</b>	*	*	*
<b>Capacitance</b>	<b>99.99mF</b>	<b>±4.0%+5digits</b>	*	*	<b>40mF</b>
<b>Temperature</b>	<b>1300°C/2372°F</b>	<b>±3.0%+5°C/9°F</b>		*	*
<b>AC/DC current clamp-on adaptor input</b>			<b>40A/400A</b>		
<b>Diode Check</b>			*	*	*
<b>Continuity Test</b>			*	*	*

**Accessories: Test leads and 9V battery, Type K temperature probe (9918T), gift box with carrying case.**