



DT-2005B/2008/20 09/2006

DT-2005B/2008/2009/2006 have double molded plastic housing and oversized high contrast

2000/4000/6000 counts LCD display with backlight.

Safety Conformance

- EN61010-1 CAT III 600V, CAT II 1000V

- Full ranges protection



Features						
Function	Max Range	Basic Accuracy	2005B	2008	2009	2006
Voltage DC	1000V	$\pm(0.5\%+2d)$	*	*	*	*
Voltage AC	700V	$\pm(1.0\%+3d)$	*	*	*	*
Current DC	20A	$\pm(1.5\%+3d)$	*	*	*	*
Current AC	20A	$\pm(2.0\%+3d)$	*	*	*	*
Resistance	20MΩ	$\pm(1.2\%+2d)$	*	*	40MΩ	60MΩ
Capacitance	200uF	$\pm(4.0\%+3d)$	*	*	100uF	6000uF
Frequency	20kHz	$\pm(1.5\%+5d)$		*	9,999MHz	9,999MHz
Temperature	760°C/1400°F	$\pm(3.0\%+3d)$		*	*	*
Diode Check	Open Voltage 2.8V dc		*	*	*	*
Continuity	Test Threshold 30Ω		*	*	*	*

Accessories : Test Leads, Type K temperature probe (2008, 2009 & 2006), 9V battery, gift box and carrying case.