



# DT-9932FC

DT-9932FC High Performance Digital Multimeters



<b>Specifications</b>			
<b>Function</b>	<b>Max Range</b>	<b>Min Resolution</b>	<b>Basic Accuracy</b>
<b>Voltage DC</b>	<b>1000V</b>	<b>0.1mV</b>	<b>±(1.2%+2d)</b>
<b>Voltage AC</b>	<b>750V</b>	<b>0.1mV</b>	<b>±(0.8%+3d)</b>
<b>Current DC</b>	<b>20A</b>	<b>0.1uA</b>	<b>±(1.5%+3d)</b>
<b>Current AC</b>	<b>20A</b>	<b>0.1uA</b>	<b>±(1.8%+5d)</b>
<b>Resistance</b>	<b>40MΩ</b>	<b>0.1Ω</b>	<b>±(1.0%+2d)</b>
<b>Capacitance</b>	<b>100uF</b>	<b>10pF</b>	<b>±(3.5%+5d)</b>
<b>Frequency</b>	<b>9.999MHz</b>	<b>0.001Hz</b>	<b>±(1.2%+3d)</b>
<b>Duty Cycle</b>	<b>99.9%</b>	<b>0.1%</b>	<b>±(1.2%+2d)</b>
<b>Temperature</b>	<b>1000°C/1832°F</b>	<b>0.1°C/°F</b>	<b>±(3%+2°C/°F)</b>
<b>Diode Check</b>	<b>1.5VDC test 0.3mA current</b>		

**Accessories: Rubber holster, Test leads, K-type temperature probe, 9V battery, RS-232 PC cable and Software diskette, Gift box with carrying case**