



DT-920/920N/920L

**/921/921N/922/92
0H/922H/931H/93**

2H

**DT-920/920N/920L/921/921N/922/92
0H/922H/931H/932H Compact True
RMS Digital Multimeters**



Features							
	920/920N/9 20L	921/921 N	920H	922	922H	931H	932H
Digital display counts	2000	2000	2000	4000	4000	6000	6000
True RMS measurements					*	*	*
Backlight	920L					*	*
Data Hold/REL measurements	Hold	Hold		Hold	*	Hold	Hold
LoZ low impedance measurement							*
Auto Power Off				*	*	*	*
Fast and accurate capacitance measurement					*	*	*
Auto Ranging		*		*	*	*	*
MAX/MIN Hold		MAX				*	*
Duty Cycle					*		*
Non-Contact ACV detection (NCV)	920N	921N	*			*	*
Motor shaking & LED indicatore for NCV detection						*	
61-segments analog bargraph						*	*
Test 1.5V and 9V batteries			*				
Full ranges protection			*		*	*	*

Specifications

Function	Max Range	Basic Accuracy	920/920N /920L	921/N	920H	922	922H	931H	932H
Voltage DC	600V	±0.5%	*	*	*	*	*	1000 V	1000 V
Voltage AC	600V	±1.2%	*	*	*	*	*	1000 V	1000 V
Current DC	10A	±2.5%	*	*	*	*	*	*	*
Current AC	10A	±3.0%		*		*	*	*	*
Resistance	2MΩ	±0.8%	*	20MΩ	*				
	40MΩ	±0.8%				*	*		
	60MΩ	±2.0%						*	*
Capacitance	99.99mF	±3.0%					100μ F	4mF	*
Frequency	10MHz	±1.5%					*	9.999 MHz	*
Temperature	760°C/1400°F	±1.5%		921N			*	*	*
Duty Cycle	99.9%	±1.2%				*	*		*
Diode Check			*	*	*	*	*	*	*
Continuity Test			*	*	*	*	*	*	*

Applications




Compact Digital Multimeters

DT-920/920L/921/922/920N/921N Series are compact multimeters with double molded plastic housing and over sized high contrast 2000/4000 counts LCD display. They're all CAT III rated for 600V and have auto-ranging function and provide 0.5% basic DCV accuracy.

Safety Conformance

- EN61010-1 CATIII 600V
- Double molded plastic housing
- Full ranges protection

• Double molded plastic housing
• Built-in Non-Contact AC Voltage Detector (920N/921N)
• 0.5% basic DC accuracy

Accessories: Test leads, 9V battery, type K temperature probe (921/921N/922/922H/931H/932H) and gift box with carrying case.