



DT-960/960B/960C /960BL/960BT/960 BT6/961/962/964/ 966

DT-960/960B/960C/960BL/960BT/960
BT6/961/962/964/966 Series

are True RMS compact digital
multimeters with double molded plastic

housing and over sized high contrast
4000 counts LCD display. They're

all CAT III rated for 600V.

Safety Conformance

- EN61010-1 CATIII 600V
- Double molded plastic housing
- Full ranges protection












Features										
	960	960B	960B L	960B T	960B T6	961	962	964	966	960C
Digital display counts	4000	4000	2000	4000	6000	4000	4000	6000	6000	6000
Display type(Negativity display)	*	Positive	Positive	Positive	Positive	*	*	*	Positive	Positive
True RMS measurements	*	*	*	*	*	*	*	*	*	*
Safety design	*	*	*	*	*	*	*	*	*	*
Data Hold/ MAX/MIN recording mode	*	*	*	*	*	*	*	*	*	*
Flash light/ Backlight	*	*	*	*	*	*	*	*	*	*
Auto Ranging & Auto Power Off	*	*	*	*	*	*	*	*	*	*
Type K temperature input						*		*	*	
Bluetooth interface with Meterbox pro software				*	*				*	*
LoZ: low input impedance to prevent ghost voltage							*	*		

Specifications

Function	Max Range	Basic Accuracy	960	960B	960BL	960BT	960BT6	961	962	964	966	960C
Voltage DC	600V	±0.5%	*	*	*	*	*	*	*	*	*	*
Voltage AC	600V	±1.0%	*	*	*	*	*	*	*	*	*	*
Current DC	10A	±1.0%	*	*	*	*	*	*	*	*	*	*
Current AC	10A	±2.0%	*	*	*	*	*	*	*	*	*	*
Resistance	40MΩ	±1.5%	*	*	20MΩ	*	6MΩ	*	*	60MΩ	6MΩ	6MΩ
Capacitance	4000μF	±3.0%	*	*		*	6000μF	*	*	4000μF	6000μF	6000μF
Frequency	10kHz	±1.0%	*	*		*	*	*	*	*	*	*
Temperature	760°C/1400°F	±3.0%						*		*	*	
Duty Cycle	99.9%	±1.2%	*	*		*	*	*	*	*	*	*
Diode Check			*	*	*	*	*	*	*	*	*	*
Continuity Test			*	*	*	*	*	*	*	*	*	*

Applications











True RMS Compact Digital Multimeters

960/960B/960BT/961/962 Series are True RMS compact digital multimeters with double molded plastic housing and over sized high contrast 4000 counts LCD display. They're all CAT III rated for 600V.

Safety Conformance

- EN61010-1 CATIII 600V
- Double molded plastic housing
- Full ranges protection

Accessories: Test leads, 1.5V AAA x 2 batteries, type K temperature probe (961/962) and clamshell.