



DT-116/118/118B/ 119

3 in 1 e-testers

The four pocket models 116, 118, 118B and 119 are double molded plastic housing and large high contrast 2000/4000 counts LCD display. They are all CAT IV 600V safety designed plus non-contact voltage detection & flashlight.

- Double Molded housing
- CAT IV 600V
- Full range protection



- Non-Contact Voltage Detection
- Flashlight



Safety Conformance

EN61010-1 CATIII 1000V

200mA fused protection (118/118B)



EMC & LVD
EN: 61326
EN: 61010-1,
EN: 61010-02-031




Features	DT-116	DT-118	DT-118B	DT-119
Digital display counts	2000	2000	4000	2000
Safety design	*	*	*	*
Auto Ranging	*	*	*	*
Data Hold	*	*		*
Auto Power Off	*	*	*	*
Flashlight	*	*	*	*
Non-Contact Voltage detection	*	*	*	*
Pocket size	*	*	*	*

Size (H x W x D): 120mm x 55mm x 40mm


Weight: 145g

Specifications						
Function	Max Range	Basic Accuracy	DT-116	DT-118	DT-118B	DT-119
Voltage DC	600V	±0.5%	*	*	*	*
Voltage AC	600V	±1.2%	*	*	*	*
Current DC	200mA	±2.0%		*	*	
Current AC	200mA	±2.5%		*	*	
Resistance	2MΩ	±0.8%	*			
	20MΩ	±0.8%		*	40MΩ	*
Capacitance	100uF	±(3.0%±5d)			*	
Frequency	100kHz	±(0.8%±5d)			*	
NCV (VAC: 100V~600V)			*	*	*	*
Diode Check			*	*	*	*
Continuity Test			*	*	*	*

Applications






3 in 1 e-testers

The four pocket models 116, 118, 118B and 119 are double molded plastic housing and large high contrast 2000/4000 counts LCD display. They are all CAT IV 600V safety designed plus non-contact voltage detection & flashlight.

Safety Conformance

- EN61010-1 CATIII 1000V
- 200mA fused protection (118/118B)

- Double Molded housing
- CAT IV 600V
- Full range protection

- Non-Contact Voltage Detection
- Flashlight

Accessories: Test leads, two "AAA" batteries and clamshell