



UT89XD Digital Multimeter

UT89X/UT89XD is a reliable hand-held 3 5/6 bit digital multimeter with true RMS sine wave measurement. It can measure Max. 1000V DC/AC voltage, Max. 20A DC/AC current, resistance, capacitance, frequency, diode, hFE, continuity and NCV, quickly distinguishing between neutral and

live wires accurately. UT89X can measure temperature and detect neutral and live wires with a test lead. UT89XD can perform LED test. Equipped with audible and visible alarm, flashlight and auto backlight functions, this series can be used in dark environment. It attracts users with its bi-color durable case, modern exterior and multiple functions.

Specifications	Range	UT89XD
DC voltage (V)	600mV/6V/60V/600V/1000V	±(0.5%+2)
AC voltage (V)	6V/60V/600V/1000V	±(0.8%+5)
DC current (A)	60μA/6mA/60mA/600mA/20A	±(0.8%+8)
AC current (A)	60mA/600mA/20A	±(1%+12)
Resistance (Ω)	600Ω/6kΩ/60kΩ/ 600kΩ/6MΩ/60MΩ	±(0.8%+3)
Capacitance (F)	6nF/60nF/600nF/6μF/60μF/600μF/6mF/60mF/100mF	±(2.5%+20)
Frequency (Hz)	9.999Hz/9.999MHz	±(0.1%+4)
Duty cycle	0.1%~99.9%	±(2%+5)
Features		
Display count		6000
Sampling rate		3 times/s
True RMS		√
AC voltage frequency response		45~1000Hz
AC current frequency response		45~1000Hz
LED test		√
Audible/visual alarm	V/A/Cap/Diode/hFE/NCV/Live (UT89X)/LED (UT89XD)	·
Diode/Continuity test		√
Transistor hFE		√
Dual range NCV test		√
Auto power off		√
Low battery indication		√
Data hold		√
Function selection	SELECT	√
Flashlight		V

Auto backlight		√	
General Characteristics			
Power	1.5V battery (R03) x 4		
Display	61mm x 36mm		
Product color	Red and grey		
Product net weight	345g		
Product size	189mm x 89mm x 53mm		
Standard accessories	Batteries, test lead, k-type temperature probe (UT89X)		
Standard individual packing	Gift box, English manual		
Standard quantity per carton	40pcs		
Standard carton measurement	490mm x 450mm x 340mm		
Standard carton gross weight	23.5kg		