



**UT39C+ Digital Multimeter**

UT39+ series modern digital multimeters are portable devices designed for the electrical industry. They feature overvoltage and overcurrent alarm and high voltage protection, triggered during faulty

operation. UT39C+ is suitable for HVACR maintenance with its temperature measurement feature. Designed according to CAT II 1000V/CAT III 600V safety standards.

### Applications:

Electrical industry

Specifications	Range	UT39C+
DC voltage (V)	400mV/4V/40V/400V/1000V	±(0.5%+5)
AC voltage (V)	4V/40V/400V/750V	±(0.8%+3)
DC current (A)	400uA/400mA/10A	±(0.8%+3)
AC current (A)	4mA/400mA/10A	±(1%+2)
Resistance (Ω)	400Ω/4000Ω/40kΩ/400kΩ/4MΩ/40MΩ	±(0.8%+2)
Capacitance (F)	4nF/40nf/400nF/4uF/40uF/400uF/4mF/10mF	±(4%+5)
Frequency (Hz)	10Hz~1MHz	±(1%+4)
Temperature	-40°C~1000°C	±(1%+4)
	-40°F~1832°F	±(1.5%+5)
<b>Features</b>		
Display count		4000
Transistor hFE		√
NCV		√
Diode		√
Frequency response	40Hz~400Hz	√
Range selection		Manual
Continuity test		√
Data hold		√
Backlight		√
Low battery indication		√
Auto power off		√
<b>General Characteristics</b>		
Power	1.5V battery (R03)×2	

Display	56.5mm x 36mm
Product color	Red and grey
Product net weight	330g
Product size	175mm x 83mm x 53mm
Standard accessories	Test leads, temperature probe
Standard individual packing	Gift box, English manual
Standard quantity per carton	30pcs
Standard carton measurement	390mm x 355mm x 340mm
Standard carton gross weight	14.5kg