

Component Parameter Test Instruments

A. TH2838 Series Precision LCR Meter

Features

- High accuracy: Adopt Auto-balance bridge technology, 4-terminal pair
- High stability and consistency: Up to 15 ranges
- High speed: Up to 5.6ms
- High resolution: 7-inch, 800×600
- High power:
 - Signal source: Voltage up to 20Vrms(only TH2838H)
Current up to 100mA(only TH2838H)
 - DC bias: Voltage up to ±40V(only TH2838H)
Current up to 100mA
Up to 120A when controlling 6 sets of TH1778 series DC Bias Current Source by external DC Bias interface
 - Independent Voltage Source: ±10V programmable output (only TH2838H)
- 201 Points List Sweep Function
- Multi-parameter Graphic Sweep Function
- Arithmetical operation
- 10 bins sorting, sorting result with sound and light alarm
- Huge storage space:
 - Internal: 100 groups of setting files, 10 groups of gif image files
 - External: 100 groups of setting files through USB storage
- Rich interfaces: USB HOST, USB DEVICE, LAN, HANDER, GPIB (Optional), SCANER(Optional), external DC BIAS control interface
- High compatibility: Support SCPI commands, compatible with KEYSIGHT E4980A, E4980AL, HP4284A etc.

NEW



RS232	USB	LAN	HANDER	DC BIAS
standard	standard	standard	standard	standard

GPIB	SCANER
option	option

TH2838 Series

Dimension (mm): 400(W) x 132(H) x425(D)
Net weight: 15kg

Brief Introduction

■ TH2838/TH2838H/TH2838A is a new generation impedance tester adopting the most advanced auto balance bridge theory in the world at present. With its 0.05% basic accuracy, speed up to 5.6ms, 20Hz-2MHz frequency range and impedance test range up to 1GΩ, this new impedance tester can meet all test demands of components and materials, especially for testing capacitor with low D and inductor with high Q. Four-terminal pair configuration can eliminate the effect of electromagnetic coupling in test cable, to extend the low limit of low impedance test 10 times than those testers with Five-pair configuration.

TH2838/TH2838H/TH2838A supports 20V AC test signal and 40V DC Bias, new-added improved multi parameter list sweep/graphic analyze will help customers to extend the comprehensive evaluation ability on components.

TH2838/TH2838H/TH2838A is a strong tool for the design, examination, quality control and production test of electronic components. Its excellent performances and functions provide a powerful tool for circuit design and development, as well as material (electronic material and non-electronic material) research and development.

TH2838/TH2838H/TH2838A can realize various tests of commercial standards and military standards, such as IEC and MIL.

The accuracy comparison table of LCR Meter

— Automatic balance bridge(TH2838 Series) — Common LCR Meter(Take TH2829C as an example)



Brief Introduction

- Application
 - 1. Passive component
 - Impedance parameter estimation and performance analysis of capacitor, inductor, magnetic core, resistor, piezoelectric devices, transformers, chip components and network components
 - 2. Semiconductor component
 - Parasitic parameter test and analysis of LED driver integrated circuit C-VDC features of varactors Parasitic parameter analysis of transistors or integrated circuit
 - 3. Other components
 - Impedance assessment of printed circuit boards, relays, switches, cables, batteries
- 4. Dielectric material
 - Dielectric constant and loss angle evaluation of plastics, ceramics and other materials
- 5. Magnetic materials
 - Magnetic permeability and loss angle assessment of ferrite, amorphous body and other magnetic materials
- 6. Semiconductor materials
 - Dielectric constant, electric conductivity and C-V characteristics of semiconductor materials Liquid crystal cell of dielectric constant, elastic constant and C-V characteristics of liquid crystal cell

Component Parameter Test Instruments

A. TH2838 Series Precision LCR Meter

Specifications

Model	TH2838	TH2838H	TH2838A
Test Signal Source			
Output impedance	100Ω, ±1% @1kHz		
Frequency	Range	20Hz-2MHz	
	Resolution	20.0000Hz - 99.9999Hz	0.1mHz
		100.000Hz - 999.999Hz	1mHz
		1.00000kHz - 9.99999kHz	10mHz
		10.0000kHz - 99.9999kHz	0.1Hz
		100.000kHz - 999.999kHz	1Hz
		1.00000MHz - 2.00000MHz	10Hz
AC test signal		<p>Rated value(ALC OFF): Set the voltage as the Hcurr voltage when the test terminal is open Set the current as the Hcurr current when the test terminal is short Constant value(ALC ON): Keep the voltage in DUT is the same as the set value Keep the current in DUT is the same as the set value</p>	
AC signal	Voltage range	5mVrms -- 2Vrms	F≤1MHz 5mVrms-- 20Vrms F>1MHz 5mVrms -- 15Vrms
	Resolution	5mVrms -- 0.2Vrms	100μVrms
		0.2Vrms -- 0.5Vrms	200μVrms
		0.5Vrms -- 1Vrms	500μVrms
		1Vrms -- 2Vrms	1mVrms
		2Vrms -- 5Vrms	2mVrms
		5Vrms -- 10Vrms	5mVrms
	Current range	50μArms -- 20mAms	50μArms --100mAms
	Resolution	50μArms -- 2mAms	1 μArms
		2mAms -- 5mAms	2 μArms
		5mAms -- 10mAms	5 μArms
		10mAms -- 20mAms	10μArms
		20mAms -- 50mAms	20μArms
		50mAms--100mAms	50μArms
Rdc test	Voltage range	100mV — 2V	
	Resolution	100μV	
	Current range	0mA— 20mA	
	Resolution	1μA	
DC Bias	Voltage range	0V — ± 10V	0V — ± 40V
	Resolution	0V -- 5V	100μV
		5V -- 10V	1mV
		10V -- 20V	2mV
		20V -- 40V	5mV
	Current range	0mA— ± 100mA	
	Resolution	0 A -- 50mA	1μA
		50mA -- 100mA	10μA

Component Parameter Test Instruments

A. TH2838 Series Precision LCR Meter

Voltage source	Voltage range	-----	-10V -- 10V	-----				
	Resolution	-----	1mV	-----				
	Current range	-----	-45mA -- +45mA	-----				
	Output impedance	-----	100Ω	-----				
Display								
Dimensions /typ		7-inch (diagonal)TFT LCD display						
Proportion		16:9						
Resolution		800×RGB×480						
Test function								
Test parameter		Cp-D,Cp-Q,Cp-G,Cp-Rp Cs-D,Cs-Q,Cs-Rs Lp-D, Lp-Q, Lp-G, Lp-Rp, Lp-Rdc Ls-D, Ls-Q, Ls-Rs, Ls-Rdc, Rdc R-X, Z-θd, Z-θr G-B, Y-θd, Y-θr Vdc-Idc						
Mathematics function		A(X+B)+C, X is test parameter, A, B,C is input parameter						
Equivalent circuit		Series, parallel						
Deviation measurement		Absolute deviation Δ compared with the nominal value Percentage deviation Δ% compared with the nominal value						
Calibration function		OPEN, SHORT, LOAD						
Range selection		AUTO, HOLD						
Range	LCR	100mΩ, 1Ω, 10Ω, 20Ω, 50Ω, 100Ω, 200Ω, 500Ω, 1kΩ, 2kΩ, 5kΩ, 10kΩ, 20kΩ, 50kΩ, 100kΩ, total 15 ranges						
	Rdc	1Ω, 10Ω, 20Ω, 50Ω, 100Ω, 200Ω, 500Ω, 1kΩ, 2kΩ, 5kΩ, 10kΩ, 20kΩ, 50kΩ, 100kΩ, total 15 ranges						
Trigger mode		INT, MAN, EXT, BUS						
Trigger delay		0 s -- 999 s, resolution 100us						
Test terminal configuration		Four-pair						
Test cable length		0m, 1m						
Test average		1-255 times						
Test time (ms)	Speed mode	20Hz	100Hz	1kHz	10kHz	100kHz	1MHz	2MHz
	FAST	330	100	20	7.7	5.7	5.6	5.6
	MED	380	180	110	92	89	88	88
	LONG	480	300	240	230	220	220	220
Test display range		$a \times 10^{-18}$; E $\times 10^{18}$						
Cs, Cp		$\pm 1.000000 \text{ aF} -- 999.9999 \text{ EF}$						
Ls,Lp		$\pm 1.000000 \text{ aH} -- 999.9999 \text{ EH}$						
D		$\pm 0.000001 -- 9.999999$						
Q		$\pm 0.01 -- 99999.99$						
R, Rs, Rp, X, Z, Rdc		$\pm 1.000000 \text{ aΩ} -- 999.9999 \text{ EΩ}$						
G,B,Y		$\pm 1. 000000 \text{ aS} -- 999.9999 \text{ ES}$						
Vdc		$\pm 1.000000 \text{ aV} -- 999.9999 \text{ EV}$						
Idc		$\pm 1.000000 \text{ aA} -- 999.9999 \text{ EA}$						
θ r		$\pm 1.000000 \text{ a rad} -- 3.141593 \text{ rad}$						
θ d		$\pm 0.0001 \text{ deg} -- 180.0000 \text{ deg}$						
Δ%		$\pm 0.0001\% -- 999.9999\%$						
t		$-99.99^\circ \text{ C} -- 1000.00^\circ \text{ C}$						

Component Parameter Test Instruments

A. TH2838 Series Precision LCR Meter

Turn Ratio (extension pending)	$\pm 0.000000 \text{ -- } 1000.000$	
Basic test accuracy	0.05% (the details refer to the instruction)	
List sweep		
Sweep points	Up to 201 points	
Sweep Parameters	Test frequency, AC voltage, AC current, DC BIAS voltage, DC BIAS current	
Trigger mode	SEQ	Once triggered, test at the sweep points. /EOM/INDEX will be output one time.
	STEP	Once triggered, test at one sweep point. /EOM/INDEX will be output at each point, but the list sweep comparator results only be output at the last /EOM.
List sweep comparator	Set one pair of lower limit and upper limit for each sweep point. Optional: judge through the first sweep parameter / judge through the second sweep parameter / not used in each limit.	
List sweep time tag	In SEQ mode, set the trigger point to 0, by defining the time, the test start time can be recorded at each measurement point.	
Graph sweep analysis		
Sweep points	51, 101, 201, 401 or 801	-----
Sweep trace	Primary or secondary parameters	-----
Display range	AUTO, HOLD	-----
Coordinate scale	Logarithm, linearity	-----
Sweep parameters	Test frequency, ACV, ACI, DCV BIAS/DCI BIAS, DC voltage source	-----
Sweep result display	Maximum value/ minimum value of primary/secondary parameter, primary/secondary value of the setting point	-----
Sweep graph storage	Sweep graphs can be saved to the interior FLASH, external USB storage or uploaded to the upper computer.	-----
Comparator		
Bin sorting	Primary parameter	9 BIN, OUT_OF_BINS, AUX_BIN, LOW_C_REJECT
	Secondary parameter	HIGH, IN, LOW
Bin limit setup	Absolute value, deviation value, percentage deviation value	
Bin count	0 -- 999999	
PASS/FAIL indication	When the primary parameter is one of the 9 BINs and the secondary parameter is IN, the PASS light on the front panel is ON, or FAIL light is ON.	
Test auxiliary function		
Data buffer storage function	201 test results can be read in batches	
Storage/Calling function	100 groups of test setting files in the internal nonvolatile memory 0--99 100 groups of test setting files in the USB storage 0—99	
Keyboard lockout function	Front panel keys can be locked	
USB HOST port	Universal Serial Bus socket, A class; FAT16/FAT32 format. USB flash disk storage or barcode scanning	
USB DEVICE port	Universal Serial Bus socket, small size B class (4 contact position); Correspond to USBTMC-USB488 and USB 2.0 The female joint is used for connecting the external control unit.	
LAN	10/100BaseT Ethernet, 8pins, two selectable speed mode	
HANDLER interface	Be used for bin sorting signal output	
External DC BIAS control	Control TH1778/TH1778S Bias current source, at most 1 set of TH1778+5 sets of TH1778S (120A MAX)	
RS232		
GPIB (option)	24 pin D-Sub port (D-24 class), the female joint is compatible with IEEE488.1, 2 and SCPI.	
SCANNER		