







UT139E Digital Multimeter

UT139 series are CAT III 600V digital multimeters designed for electricians. Its NCV feature can effectively check electrical status through measuring EM field intensity. The new UT139E/S models include special features such as LoZ (ACV) for measuring ghost' voltage. Its built-in 31-segment

analog bar also gives electricians a better visual representation of measurement results. UT139S is built with black EBTN display and it is a perfect meter for working in dark environments.

Applications:

It can work in dark environment.

Specifications	Range	UT139E
DC voltage (V)	600V	±(0.5%+2)
AC voltage (V)	600V	±(0.8%+3)
DC current (A)	10A	±(0.7%+2)
AC current (A)	10A	±(1%+3)
Resistance (Ω)	60ΜΩ	±(0.8%+2)
Capacitance (F)	99.99mF	±(4%+5)
Frequency (Hz)	10Hz~10MHz	±(0.1%+4)
Temperature (°C)	-40°C~1000°C	±(1%+4)
Temperature (°F)	-40°F~1832°F	±(1.5%+5)
Features		
Display count		6000
Auto range/Manual range /True RMS		√
Bandwidth (Hz)		45Hz~400Hz
NCV/Continuity buzzer		√
Duty cycle	0.1%~99.9%	√
Diode		Around 3V
LPF/LoZ (ACV)		√
Analog bar		√
General Characteristics		
Power	1.5V battery (R6) x 2	
Display	58mm x 36mm	
Product color	Red and grey	
Product net weight	345g	

Product size	170mm x 80mm x 48mm
Standard accessories	Batteries, test leads, temperature probe
Standard individual packing	Gift box, English manual
Standard quantity per carton	20pcs
Standard carton measurement	450mm x 330mm x 340mm
Standard carton gross weight	12.2kg