



UT125C Digital Multimeter

UT125C is a pocket size, ergonomic and reliable multimeter with 4000 display counts. It is a useful tool for electronics DIYers working with low currents ($< 0.4\text{A}$). This product is CE/cETLus certified and complies with CAT III 600V.

| Specifications | Range | UT125C |
|------------------------------|--------------------------|-----------|
| DC voltage (V) | 600V | ±(0.5%+5) |
| AC voltage (V) | 600V | ±(1.2%+5) |
| DC current (A) | 400mA | ±(1.8%+5) |
| AC current (A) | 400mA | ±(2%+8) |
| Resistance (Ω) | 40MΩ | ±(1%+5) |
| Capacitance (F) | 100μF | ±(4%+10) |
| Frequency (Hz) | 10Hz~60kHz | ±(0.1%+5) |
| Duty cycle | 20%~80% | Reference |
| Features | | |
| NCV | | √ |
| Diode test/Continuity test | | √ |
| Low battery indication | | √ |
| Data hold/Auto power off | | √ |
| Operating temperature | 0°C~50°C | |
| General Characteristics | | |
| Power | 1.5V battery (R03) x 2 | |
| Display | 38mm x 23mm | |
| Product color | Red and grey | |
| Product net weight | 180g | |
| Product size | 112mm x 58mm x 35mm | |
| Standard accessories | Batteries | |
| Standard individual packing | Gift box, English manual | |
| Standard quantity per carton | 60pcs | |
| Standard carton measurement | 500mm x 290mm x 280mm | |
| Standard carton gross weight | 13.1kg | |