



UT33A+ Palm Size Multimeter

The new generation UT33+ series redefines the performance standards for entry-level digital multimeters. Our innovative industrial design ensures that these products can withstand 2 meters drop. The new LCD display layout provides a better user experience. This series ensures that users can work safely in CAT II 600V environment. Special features are, 2mF capacitance test (UT33A+); battery test (UT33B+); temperature measurement function (UT33C+); non-contact voltage (NCV) test (UT33D+).

| Specifications | Range | UT33A+ |
|-----------------------------------|--|-----------|
| DC voltage (V) | 200mV/2V/20V/200V/600V | ±(0.5%+2) |
| AC voltage (V) | 600V | ±(0.7%+3) |
| DC current (A) | 10A | ±(1%+2) |
| AC current (A) | 10A | ±(1.2%+3) |
| Resistance (Ω) | 200Ω/2kΩ/20kΩ/200kΩ /2MΩ/20MΩ/200MΩ | ±(0.8%+2) |
| Capacitance (F) | 2mF | ±(4%+8) |
| Features | | |
| Display count | | 2000 |
| Auto power off/Auto backlight off | | √ |
| Diode test/Continuity buzzer | | √ |
| 2m drop test/ Test probe holder | | √ |
| Range selection | | Auto |
| General Characteristics | | |
| Power | 1.5V battery (R03) x 2 | |
| Display | 66mm x 51mm | |
| Product net weight | Red and grey | |
| Product color | 206g (batteries included) | |
| Product size | 134mm x 77mm x 47mm | |
| Standard accessories | Batteries, test leads | |
| Standard individual packing | Gift box, English manual | |
| Standard quantity per carton | 60pcs | |
| Standard carton measurement | 640mm x 310mm x 350mm | |
| Standard carton gross weight | 18.6kg | |