



### UT33B+ Palm Size Multimeter

The new generation UT33+ series redefines the performance standards for entry-level digital multimeters. Our innovative industrial design ensures that these products can withstand 2 meters drop. The new LCD display layout provides a better user experience. This series ensures that users can work safely in CAT II 600V environment. Special features are, 2mF capacitance test (UT33A+); battery test (UT33B+); temperature measurement function (UT33C+); non-contact voltage (NCV) test (UT33D+).

Specifications	Range	UT33B+
DC voltage (V)	200mV/2V/20V/200V/600V	$\pm(0.5\%+2)$
AC voltage (V)	200V/600V	$\pm(1.2\%+3)$
DC current (A)	200 $\mu$ A/200mA/10A	$\pm(1\%+2)$
Resistance ( $\Omega$ )	200 $\Omega$ /2k $\Omega$ /20k $\Omega$ /200k $\Omega$ /20M $\Omega$	$\pm(0.8\%+2)$
Features		
Display count		2000
Auto power off/Auto backlight off		$\sqrt$
Diode test/Continuity buzzer		$\sqrt$
2m drop test/ Test probe holder		$\sqrt$
Range selection		Manual
Battery test		1.5V/9V/12V
General Characteristics		
Power	1.5V battery (R03) x 2	
Display	66mm x 51mm	
Product net weight	Red and grey	
Product color	206g (batteries included)	
Product size	134mm x 77mm x 47mm	
Standard accessories	Batteries, test leads	
Standard individual packing	Gift box, English manual	
Standard quantity per carton	60pcs	
Standard carton measurement	640mm x 310mm x 350mm	
Standard carton gross weight	19.4kg	