









DT-900A

2 in1 HCHO & TVOC Meter The HCHO
Tester provides a real time
measurement of HCHO and TVOC tech
product to meet with a variety of
occasions air pollution measurement
needs, timely responds air pollution.
This instrument has a high accuracy,
fast response, sensitivity. It is compact,
easy to carry, suitable and home,
offices, factories, hotels and schools
and other indoor environments. It can
be displayed at any formaldhyde in the air and the
concentration of TVOC, and calculate the value of API(Air
Pullution Index).

Features	
Fuel Cell. HCHO sensor, high accuracy and reliability	
LCD display with backlight	
Real-time display the concentration of HCHO in the air	
Real-time display the concentration of TVOC in the air	
Real-time display the API	
Sound and Light alarm when pollution	
Auto power off	

Specifications		
НСНО		
Range	0.00 to 5.00mg/m³	
Resolution	0.01mg/m³	
Repeatability accuracy	±2%	
TVOC		
Range	0.00 to 9.99mg/m³	
Resolution	0.01mg/m³	
Repeatability accuracy	±2%	
Operation temperature range	0°C to 50°C	
Storage temperature range	- 10°C to 60°C	
Working Voltage	7.4V(Rechargeable battery)	

Size(HxWxD): 248mm x 160mm x 100mm Weight: 584g

Accessories: Li battery, power adaptor, gift box with carrying case.